

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
verse side)E-
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0321613

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL x 810' FEL, SEC. 15 (UNIT H, SE 1/4 NE 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3248' R. D. B.

7. UNIT AGREEMENT NAME

South Mott Unit Fed.

8. FARM OR LEASE NAME

9. WELL NO.

10

10. FIELD AND POOL, OR WHOLE

FOULER BLINERY

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

15-24-37 NMPM

12. COUNTY OR PARISH

13. STATE

LEA

N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☒(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☒ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In an effort to repair 7" casing leak and restore well to production, propose as follows:

Clean out to PBD of 5320' and run 4 1/2" OD 9.5" J-55 casing from surface to 5320' and cement w/ 260 yd of 100 lb. cement. perforate 5350-52 w/ 25PF and running Reiber Padlock zone w/ 100 yd cement. Drill and cleanout to PBD of 5320'. Perforate Reiber at selected intervals between 5424'-5692'. Acidize w/ 2000 gal 15% LSTNE. Frac w/ 40,000 gal gel bulk containing 1-1 1/2" sand/gal. Evaluate.

Pursuant to tele. auth. from Brown-Grady 9-1-67.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Sup

DATE

9-1-67

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

4- USGS
1- NSW
1- SSP
1- RBY
1- ATLANTIC
1- CONCO
1- STD. TX
1- TENNESSEE

*See instructions on Reverse Side

APPROVED
1967
A. H. BROWN
DISTRICT ENGINEER