

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NMI 0321613	
2. NAME OF OPERATOR American Petroleum Corp.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 68 Hobbs, NM. 88240		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FNL X 810' FEL, Sec. 15 (1/4 NW 1/4, SE 1/4 NE 1/4)		8. FARM OR LEASE NAME South Mott Unit	
14. PERMIT NO.		9. WELL NO. 10	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3248' RDB		10. FIELD AND POOL, OR WILDCAT South Mott Unit	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 15-24-37 10MPM	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*		12. COUNTY OR PARISH Rea	
		13. STATE NM	

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In accordance with Form 9-330 submitted 10/20/64
Recompleted in Blinley after abandoning middle
work done.

"Squeezed" sand pack preparations 4878-94 with 150
lb. cement. Drilled out to 6000'. Set casing with
Bridge Plug at 5820'. Logged. Reported Blinley
intervals 5424-34, 5436-60, 5470-72, 5498-5501,
5516-18, 5558-62, 5598-5601, 5614-18, 5664-72, 5690-92
w/215PF. Acidized with 2000 gallons.
Evaluated.

On PT 12/7/64 flowed 25 BC x 43W in 24 hours
Flow 24/64" Choke. TPAV 5424, TPF 600-100. Log 369
CG 10-23-64

18. I hereby certify that the foregoing is true and correct

SIGNED

Original Signed by:

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DEC 21 1964

J. L. GORDON
ACTING DISTRICT ENGINEER

5-USGS-Hobbs

1-JTD TEX-HOUSTON

1- " " - MIDLAND

1- CONOCO-HOBBS

1-JWB

1-SUSP

1-F

1-STATELAND-SF *See Instructions on Reverse Side

1-ATLANTIC

1-TENNECO