

NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting or test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON RESULT OF PLUGGING AND ABANDONING	XX

April 7, 1952 Hobbs, New Mex.

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation J. R. Holt Well No. 1 in the
 Company or Operator Lease
 SW SE of Sec. 16 T. 24S R. 37E N. M. P. M.,
 Langlie-Mattix Pool Lea County.

The dates of this work were as follows: Completed April 1, 1952

Notice of intention to do the work was ~~was not~~ submitted on Form C-102 on March 16, 1952, and approval of the proposed plan was ~~was not~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Total Depth 3548'. 7" casing set at 3395'. 10-3/4" casing set at 232'. Open hole size 6-1/4". 8-3/4" hole 239'-3400'. Rustler formation 1070-1170'. Top salt 1170'. Base salt 2440'. Queen formation 3310-3548'.

PROCEDURE USED IN PLUGGING

1. Filled hole with heavy mud.
2. Ran 7" Model K Baker cement retainer set at 3370' and squeeze cemented below retainer with 50 sacks cement.
3. Shot off 7" casing at 2305' and pulled same.
4. Spotted cement plug from 2160-2110'. 19 sacks cement.
5. Spotted cement plug from 1122'-990'. 50 sacks cement.
6. Placed bridge at 97' and filled 10-3/4" casing with cement from 97' to 0'. Set 4" marker extending 4' above ground level.

Witnessed by J. R. Tate Gulf Oil Corporation Production Foreman
 Name Company Title

APPROVED:
 OIL CONSERVATION COMMISSION

Roy J. W. W. W.
 Name
 Title
 APR 12 1952
 Date

I hereby swear or affirm that the information given above is true and correct.

Name *Char Taylor*
 Position Area Prod. Supt.
 Representing Gulf Oil Corporation
 Company or Operator
 Address Box 2167, Hobbs, New Mexico