NUMBER OF COPI	ES RECE	IVED	·	
10	STRIBUT	ION		
SANTA FE				
FILE				
U.S.G.S.		 		
LAND OFFICE		+		
TRANSPORTER	OIL	 		
	GAS			
PRORATION OFFIC	E			
OPERATOR				

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES M'64

	Indicate Nature of Notice by Checki	ng Below
Notice of Intention to Change Plans	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper
Notice of Intention To Plug Well	Notice of Intention to Plug Back	Notice of Intention to Set Liner
Notice of Intention to Squeeze	Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)
Notice of Intention to Gun Perforate	Notice of Intention (Other 10 Whitehook X	Notice of Intention (Other)
OIL CONSERVATION COMMISS SANTA FE, NEW MEXICO	ION Hobbs, New Mexico	July 15, 1964 (Date)
Gentlemen:		(Date)
Following is a Masica of Toward		
Amondana Daka 2	n to do certain work as described below at the	
(Company or	Oration C. Myore nes	Well No. 24 in (Unit)
74 of Sec 2	T24-S F87-E XX	(Unit) PM. Jowler Devortian
(40-acre subdivision)	_	
	County.	d. Lease # NH 037667
		- · · · · · · · · · · · · · · · · · · ·
	FULL DETAILS OF PROPOSED PLAN	N OF WORK
(FO	FULL DETAILS OF PROPOSED PLAN LLOW INSTRUCTIONS IN THE RULES AN	N OF WORK
	LLOW INSTRUCTIONS IN THE RULES AN	N OF WORK ND REGULATIONS)
D 5310'. Pursuant to t	alsphone approval of 7-14-64, M	N OF WORK ND REGULATIONS) Sign of the NMOCC
D 5310'. Pursuant to t	alsphone approval of 7-14-64, M	N OF WORK ND REGULATIONS) Signal of the NMOCC
D 5310'. Pursuant to t and 8. J. Smith, it is p	elephone approval of 7-14-64, Marchael to set cement plugs at	N OF WORK ND REGULATIONS) SERVE FOR THE NAME OF THE SERVE OF
O 5310'. Pursuant to t and 8. J. Smith, it is p 5310'-5235'; 25 sk; 496	elephone approval of 7-14-64, Me reposed to set cement plugs at 0'-4885; 25 ex; 4500'-3900' ap	N OF WORK ND REGULATIONS) SHEEP PARAMETERS of the NMOCC the following depths: PROX 120 ex; and set a whipstock
O 5310'. Pursuant to t and 8. J. Smith, it is p 5310'-5235'; 25 sk; 496	elephone approval of 7-14-64, Me reposed to set cement plugs at 0'-4885; 25 ex; 4500'-3900' ap	N OF WORK ND REGULATIONS) SHEEP PARAMETERS of the NMOCC the following depths: PROX 120 ex; and set a whipstock
ID 5310'. Pursuant to tond 8. J. Smith, it is possible 5310'-5235'; 25 sm; 496 on top of the plug at 396	alephone approval of 7-14-64, Me reposed to set cement plugs at 0'-4885; 25 sx; 4500'-3900' appoint to correct excessive deviations.	N OF WORK ND REGULATIONS) SHEEP PARAMETERS of the NMOCC the following depths: PROX 120 ex; and set a whipstock
nd 3. J. Smith, it is possible of the plug at 390 the plug at 390	elephone approval of 7-14-64, Me reposed to set cement plugs at 0'-4885; 25 ex; 4500'-3900' ap	N OF WORK ND REGULATIONS) SHEEP PARAMETERS of the NMOCC the following depths: PROX 120 ex; and set a whipstock
D 5310'. Pursuant to t and 8. J. Smith, it is p 310'-5235'; 25 sm; 496 In top of the plug at 396	alephone approval of 7-14-64, Me reposed to set cement plugs at 0'-4885; 25 sx; 4500'-3900' appoint to correct excessive deviations.	N OF WORK ND REGULATIONS) SHEEP PARAMETERS of the NMOCC the following depths: PROX 120 ex; and set a whipstock
D 5310'. Pursuant to tond 8. J. Smith, it is possible of the plug at 390 opth. The current total	alsphone approval of 7-14-64, Me roposed to set cement plugs at 0'-4885; 25 sx; 4500'-3900' approval to correct excessive deviated depth of the well is 5310'.	N OF WORK ND REGULATIONS) SHEEP PARAMETERS of the NMOCC the following depths: PROX 120 ex; and set a whipstock
D 5310'. Pursuant to t and 8. J. Smith, it is p 310'-5235'; 25 sm; 496 In top of the plug at 396	alsphone approval of 7-14-64, Me roposed to set cement plugs at 0'-4885; 25 sx; 4500'-3900' approval to correct excessive deviated depth of the well is 5310'.	N OF WORK ND REGULATIONS) SHEEP PARAMETERS of the NMOCC the following depths: PROX 120 ex; and set a whipstock
and 8. J. Smith, it is p 5310'-5235'; 25 sm; 496 on top of the plug at 396 depth. The current total	alsohome approval of 7-14-64, Marophome approval of 7-14-64, Marophome approval of 7-14-64, Marophome approval of 7-14-64, Marophome approval to set cement plugs at 0'-4885; 25 sx; 4500'-3900' approved to correct excessive deviated depth of the well is 5310', approved the well is 5310'.	N OF WORK ND REGULATIONS) SHEEP PARAMETERS of the NMOCC the following depths: PROX 120 ex; and set a whipstock

Approved, 19, 19	Fan American Petroleum Corporation Original Signed Blany or Operator
	ByV. E. STALEY,
Approved OIL CONSERVATION COMMISSION	Position 192 Superintendent Send Communications regarding well to:
Ву	Name V. Staley
Title	AddreiBox 68 - Hobbs, New Mexico - 98240
opies Gulf - Hobbs	100100 = 30240