

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
AMT. FE	
FILL	
U.S.G.P.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
WELL LOCATION AND ACREAGE DEDICATION PLAT
 SEE INSTRUCTIONS FOR COMPLETING THIS FORM ON THE REVERSE SIDE

FORM C-128
 Revised 5/1/57

OCT 13 1964


SECTION A

Operator Pan American Petroleum Corporation		Lease USA C. Myers #B		Well No. 24
Unit Letter	Section	Township	Range	County
		24-S	37-E	Lea
Actual Footage Location of Well: feet from the South line and 1650 feet from the East line Ground Level Elev. 330 Producing Formation Blinn Pool Fowler Blinn Dedicated Acreage: 80 Acres				

1. Is the Operator the only owner in the dedicated acreage outlined on the plat below? YES ☒ NO ☐ ("Owner" means the person who has the right to drill into and to produce from any pool and to appropriate the production either for himself or for himself and another. (65-3-29 (e) NMSA 1935 Comp.)
2. If the answer to question one is "no," have the interests of all the owners been consolidated by communitization agreement or otherwise? YES ☐ NO ☐ If answer is "yes," Type of Consolidation _____
3. If the answer to question two is "no," list all the owners and their respective interests below:

Owner	Land Description

SECTION B



CERTIFICATION

I hereby certify that the information in SECTION A above is true and complete to the best of my knowledge and belief.

Name	Charles E. Myers
Position	Area Superintendent
Company	Pan American Petroleum Co
Date	October 8, 1964

I hereby certify that the well location shown on the plat in SECTION B was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed	
Registered Professional Engineer and/or Land Surveyor	
Certificate No.	

INSTRUCTIONS FOR COMPLETION OF FORM C-128

1. Operator shall furnish and certify to the information called for in Section A.
2. Operator shall outline the dedicated acreage for *both* oil and gas wells on the plat in Section B.
3. A registered professional engineer or land surveyor registered in the State of New Mexico or approved by the Commission shall show on the plat the location of the well and certify this information in the space provided.
4. All distances shown on the plat must be from the outer boundaries of the Section.
5. If additional space is needed for listing owners and their respective interests as required in question 3 of Section A, please use space below.

COUNTY	LEA	FIELD	Fowler-Blinebry	STATE	N.M.
OPR	PAN AMERICAN PETROLEUM CORPORATION				MAP
24 Myers, C.-Federal "B"					
Sec. 9, T-24-S, R-37-E				CO-ORD	
330' fr S Line & 1650' fr E Line of Sec.					
Spud 6-28-64		CLASS		EL 3282	
Comp 9-27-64		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
10 3/4"	350'	300	Bli 5430		
7 5/8"	3460'	200	Tubb 6063		
4 1/2"	7714'	600	Abo 6590		
			Wdfd 7562		
			Dev. 7692		
LOGS EL GR RA IND HC A					
		TD 7737', PBD 7646'			

IP Blinebry Perfs 5513-5599' Pmpd 22 BOPD + 69 BW. Pot. Based on 24 hr test, gravity 37.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Cactus Drlg. Co.	PROP DEPTH 7800'	TYPE
DATE			

F. R. 6-25-64; Oper's Elev. 3284' KB.
PD 7800' - Devonian.
Contractor- Cactus Drlg. Co.

6-29-64 TD 350', WOC.
7-6-64 Drlg. 2759'.
7-13-64 Drlg. 4850'.
7-20-64 TD 5310', drld. by @ 4057'.
Set Whipstock @ 3956'.
7-27-64 Drlg. 6041'.
8-3-64 TD 7704', prep to run logs.
8-10-64 TD 7718', tstg.
Perf. 7692-7702' w/2 SPF.
Ac. 1000 gals.
Swbd. 57 BLW/6 hrs.

8-17-64 TD 7718', PB 7703', tstg.
Swbd. 87 BLW + 128 BNW/24 hrs.
Sq. Perf. 7692-7702' w/100 sx.
Re-Perf. 7692-7702' w/2 SPF.
Ac. 500 gals.
Swbd. 43 BLW + 35 BNW/5 hrs.

8-24-64 TD 7718', PBD 7699', swbg.
 Sq. Perfs 7692-7702' W/100 sx.
 Re-Perf 7692-98' W/2 SPF
 Ac. 500 gals.
 Swbd 42 BLW, 3 BO + 258 BNW/39 hrs.
8-31-64 TD 7718', PBD 7699', SI.
9-8-64 TD 7718', PBD 7699', SI.
9-14-64 TD 7737', prep to squeeze
 Deepened 7718-7737'
 Swbd 43 BLW + 154 BNW/16 hrs (7692-7737')
9-21-64 TD 7737', PBD 7646', RU Pump.
 Squeezed Devonian Perfs 7692-98' & OH 7714-37'
 W/100 sx.
 DO to 7646'
 Perf (Blinebry) 5513-24', 5540-60', 5590-99'

 W/2 SPF
 Ac. 6000 gals.
 Swbd 20 BO + 49 BW/10 hrs.
9-28-64 TD 7737', PBD 7646', COMPLETED.
 Pmpd 31 BO + 129 BW/19 hrs.