

COUNTY	LEA	FIELD	Fowler	STATE	NM
OPR	PAN AMERICAN PETROLEUM CORP.				MAP
	20 South Mattix Unit-Federal				
	Sec. 15, T-24-S, R-37-E				CO-ORD
	1980' FNL, 660' FWL of Sec.				MN 21678
	Spd 3-15-66		CLASS	EL [REDACTED]	
	Cmp 4-9-66		FORMATION	DATUM	FORMATION DATUM
CSG & SX - TUBING					
8 5/8"	1014'	475			
4 1/2"	5750'	610			
LOGS EL GR RA IND HC A					
			TD 5750', PBD 5716'		

IP Blinebry Perfs 5430-5688' Flwd 193 BOPD + 83 BLW. Pct. Based on 24 hr test thru 17/64" chk., TP 560#, CP 1400#, Gravity 38., GOR 955.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drilg. Co.	PROP DEPTH 5750'	TYPE
DATE		

F.R. 2-24-66; Opr's Elev. 3270' KB
 PD 5750' - Blinebry
 Contractor - Cactus Drilg. Co.
 3-21-66 Drilg. 3545'.
 3-28-66 Drilg. 5490'.
 4-4-66 TD 5750', PBD 5716', prep to frac.
 Perf 5430-32', 5436-40', 5463-64', 5497-98',
 5523-24', 5530-31', 5541-45', 5554-56',
 5578-80', 5582-88', 5602-03', 5623-24',
 5634-39', 5648-50', 5664-67', 5686-88'
 W/2 SPT
 Ac (5430-5688') 2000 gals; IR 4.2 BPM
 Swbd 14 BO + 13 BLW/12 hrs.
 4-11-66 TD 5750', PBD 5716', COMPLETE.
 Frac (5430-5688') 30,000 gals brine +
 sd. IR 50 BPM