

Form 10-66
May 1966UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE
FIELD INSTRUCTIONS
VERSE 2000Form Approved
Bureau Pattern No. 42-11424
U. S. LEASE TERMINATION AND SECURITY NO.LC032450(b)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUDDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for production or disposal of water or oil from a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. GIL WELL ☐ GAS WELL ☐ OTHER <u>Drilling</u>		7. UNIT AGREEMENT NAME <u>SOUTH MATTHEW UNIT FEDERAL</u>	
2. NAME OF OPERATOR <u>PAN AMERICAN PETROLEUM CORPORATION</u>		8. FARM OR LEASE NAME	
3. ADDRESS OF OPERATOR <u>Box 66, Hobbs, New Mexico</u>		9. WELL NO. <u>21</u>	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also 11 or 12 below.) At surface:		10. FIELD AND POOL, OR WILDCAT <u>FOULER ELLENBURGER</u>	
1873.3' FSL x 2086.7' FWL Sec. 15 (UNIT K, NE 1/4 SW 1/4)		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>15-24-37 N M PM</u>	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH <u>LEA</u>	13. STATE <u>N.M.</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Davidson Bros. Drilg. Co. spudded 17 1/2" hole
2:30 PM, 9-28-66. On 9-29-66, 13 3/8" OD 48" S-40
casing was set at 312' w/ 350 st. Cement Circ.
After NOC 18 hours, tested casing w/ 1000 psi
for 30 minutes. Test O.K.

Reduced hole to 12 1/4" at 312' and
resumed drilling operations.

RECEIVED
OCT 5 1966
U.S. GEOLOGICAL SURVEY
INTERIOR DEPARTMENT

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

OCT 6 1966

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

4- USGS- HZT
1- NSW
1- SUSP
1- IRY
1- STATE LAND
1- CONOCO
1- ATLANTIC
1- TENNECO
1- TEXAS