

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIPlicate*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.GEOLOGICAL SURVEY
HOBBS OFFICE O.C.C.5. LEASE DESIGNATION AND SERIAL NO.
LC-032450(6)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or deepen a well back to a different reservoir.
Use "APPLICATION FOR PERMIT TO DRILL" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBAL NAME

7. UNIT AGREEMENT NAME
**SOUTH MATTHEW
UNIT FEDERAL**

8. FARM OR LEASE NAME

9. WELL NO.

2210. FIELD AND POOL, OR WILDCAT
FOWLER Blinberry11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**15-24-37 NMPM**12. COUNTY OR PARISH
Lea13. STATE
N.M.

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling	14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3263' RDB
2. NAME OF OPERATOR San American Petroleum Corp.		
3. ADDRESS OF OPERATOR Box 68 Hobbs, New Mexico 88240		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1930' FWL X 710' FNL, Sec. 15 (Unit C, NE 1/4 NW 1/4)		

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) **Completion** ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 4 1/2" OD J-55 9.5" Casing at 5750' w/300 ex. 8% Gel and 250 ex Meat. After approx. 28 hours tested casing w/2000 PSI for 30 minutes. Test O.K. Perforated intervals 5430-32, 47-51, 70-71, 87-88, 89-91, 5530-32, 52-54, 56-58, 84-87, 92-94, 5626-28, 42-43, 45-46, 60-62 w/2JSPF. Acidized w/2000 gal. Frac- 40,000 gal gel brine, 60,000# sand, 4000# glass beads tail-end.

On PT. Flow 129 B0X 6684W 24 hours 1 1/4" choke. Cgr 39° TPF 800, CPF 1325. GOR 820.

TD-5750

comg. 11-24-66

PBD-5710

TPH-5430 Blinberry

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Foreman

DATE

11-28-66

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

NOV 29 1966

*See Instructions on Reverse Side

J L GORDON
ACTING DISTRICT ENGINEER

04-4-USGS-H
1-NSW
1-SUSP
1-BRY
1-ATLANTIC
1-CONOLD
1-TEXNECO
1-STD OF TEX
1-STATE LAND