

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLI E*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. LC-032418 (4)	
2. NAME OF OPERATOR Sidney Lemier		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR c/o Oil Reports & Gas Services, Inc., Box 763, Hobbs, NM 88240		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 330° FNL & 1650° FKL of Section 35		8. FARM OR LEASE NAME I. D. Qaz "A"	
14. PERMIT NO.		9. WELL NO. 6	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3290 KB		10. FIELD AND POOL, OR WILDCAT Jalisco	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 15, T24S, R34E	
		12. COUNTY OR PARISH Lea	
		13. STATE N.M.	

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Deepen & Run Limer	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Work began 3/17/76. Deepened from 3145 to 3190. Set 3 1/2" OD liner at 3190 with top at 2630 with 40 sacks Latex cement. Squeezed top of liner with 30 sacks Latex cement, 4% gel. WOC 48 hours, drilled out cement to 3190. Pressure tested casing with 1000# for 30 minutes, test O.K. Perf 3150 & 3151 with 2 holes. Sub 100% water. Set cast iron bridge plug at 3140 capped with 5' cement. Perf 2902, 04, 13, 19, 35, 36, 50 & 2952 with 8 holes. Treated with 20,000 gal gelled water, 18,000# 20/40 sand, treating pressure 1600# @ 10 bbls per min. Put on pump 7/6/76. Pumping lead water with tract of oil, approximately 50,000 MCF gas per day.

18. I hereby certify that the foregoing is true and correct

SIGNED *Harold L. Latta* TITLE Agent DATE 7/12/76

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved, accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner, or tubing pulled and the depth to top of any left in the hole; method of closing-top of well; and date well site conditioned for final inspection looking to approval of the abandonment.