

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

EXHIBIT IN THE
(Other instruction
verse side)

Form 7-66
District Engineer No. 42 (P)

5. LEASE DESIGNATION AND SURVEY NO.

LC-032450-6

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR
BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

910' FNL x 1980' FWL Sec. 15 (Unit C, NE 1/4 NW 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3261' R.D.B.

7. UNIT AGREEMENT NAME

SOUTH MATTHEW UNIT FEDERAL

8. FARM OR LEASE NAME

9. WELL NO.

25

10. FIELD AND POOL, OR WELDPART

WELDER EISENBURGER

11. SEC., T., R., or BLK. AND SURVEY OR AREA

15-24-37 NMPM

12. COUNTY OR PARISH 13. STATE

LEA

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) *WATER SHUT-OFF*

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 12-10-68, 5 1/2" OD 14-7" N-80 + J-55 was set @ (TD) 9980', Cemented in 2 stages w/ DU Tool @ 7997. 1st stage cemented w/ 400 py Inferno 4% gel + 100 py. med. 2nd stage - 800 py Inferno 4% gel. Tested casing w/ 3500 psi, 106 30 min. Test O.K. After 24 hours, drilled out to 9955' (PBD) and perforated interval 9925-42' w/ 215 PF. Acidized w/ 1000 gal 15% HCl. Evaluated.

PT. Flowed 251 BO x 16 BW 24 hours. 23 1/4" CN. 481 MCF6, GOR 1920 TDF-150

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AREA SUPERINTENDENT

DATE 12-18-68

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 23 1968

*See Instructions on Reverse Side

J L GORDON
ACTING DISTRICT ENGINEER

4- USGS-A
1- NSW
1- SUSP
1- RRV
1- ATL
1- CONOCO
1- TENNECO
1- STD OF TEX
1- STATE LAND