

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 4190	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____ 5096	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____ 5510	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____ 6102	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____ 6296	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____ 6746	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
Surface	216		Surface sand & caliche				
216	1060		Red Bed				
1060	1410		Anhydrite & Red Bed				
1410	2600		Anhydrite & Salt				
2600	2910		Anhydrite & Lime				
2910	2980		Anhydrite				
2980	3405		Anhydrite & Lime				
3405	5096		Dolomite & Lime				
5096	5510		Sandy Lime & Dolomite				
5510	6102		Dolomite				
6102	6296		Sandy Lime w/Shale Stringers				
6296	6740		Dolomite				
6740	6950		Dolomite & Lime				

RECEIVED

JUL 14 1972
OIL CONSERVATION COM.
HOUSTON, TEXAS