

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| | | |
|--|--|--|
| <p>SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)</p> | | <p>5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/></p> |
| <p>1. OIL WELL <input checked="" type="checkbox"/> = GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/></p> | | <p>5. State Oil & Gas Lease No.</p> |
| <p>2. Name of Operator McCulloch Oil Corporation</p> | | <p>7. Unit Agreement Name</p> |
| <p>3. Address of Operator 501 Wall Towers East, Midland, Texas 79701</p> | | <p>8. Farm or Lease Name Dalport-Hair</p> |
| <p>4. Location of Well UNIT LETTER <u>L</u> <u>554</u> FEET FROM THE <u>West</u> LINE AND <u>1874</u> FEET FROM THE <u>South</u> LINE, SECTION <u>11</u> TOWNSHIP <u>24S</u> RANGE <u>37E</u> NMPM.</p> | | <p>9. Well No. 1</p> |
| <p>15. Elevation (Show whether DF, RT, GR, etc.) NA</p> | | <p>10. Field and Pool, or Wildcat Fowler (Upper Yeso)</p> |
| <p>12. County Lea</p> | | |

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12:00 noon 5/31/72.

Reached surface TD of 1074' at 6:30 a.m. 6/1/72. Circulated 30 minutes. Set 1056.66' of 8 5/8" OD, 24#, J-55, 8rd ST&C casing at 1068.16'. Ran guide shoe, insert float, centralizers and cement basket. Cemented with 400 sx trinity lite weight and 100 sx Class "C" w/2% CaCl₂. Cement Circulated.

WOC for 24 hours.

Tested casing to 600# for 30 minutes.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Joe D. Ramey

TITLE District Manager

DATE 6/5/72

Orig. Signed by
Joe D. Ramey
Dist. I, Supv.

PROVED BY Joe D. Ramey
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE JUN 14 1972