

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC - 032339 (6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Continental Oil Company	8. FARM OR LEASE NAME Mottix
3. ADDRESS OF OPERATOR P. O. Box 460, Hobbs, NM 88240	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1830' FEL + 660' FSL of Sec 10	10. FIELD AND POOL, OR WILDCAT Fowler upper yeso
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3253' DF
	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Perf + test Paddock

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The Paddock pool was perf + tested by the following procedure.

Set bridge plug at 5210'. Perf Paddock from 5080' to 5092'. Treated with 500 gals 15% acid. Placed well on test - tested only wth. lg perfs with 150 lbs of cement. Repers. from 5080' to 5087 and treated with 2,000 gals 20% acid. Placed well back on test. again tested only water. lg. perfs with 150 sacks of cement. Drilled out cement and reth. bridge plug. Returned well to production as Fowler upper yeso oil well. Work started 8-18-73 completed 9-12-73

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Admin. Supervisor

DATE 10-4-73

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

OCT 9 1973

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side