

CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.O.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-2431	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation	8. Farm or Lease Name J. R. Holt (NCT-A)
3. Address of Operator P. O. Box 670, Hobbs, NM 88240	9. Well No. 5
4. Location of Well UNIT LETTER <u>0</u> <u>810</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>16</u> TOWNSHIP <u>24S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat Langlie Mattix
15. Elevation (Show whether DF, RT, GR, etc.) 3235' GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Circulate hole with abandonment mud. Set CIBP at 3240', cap with 35' cement. Spot 100' plug 2297'-2397' and from 1150'-1250' (test this plug per OCD request). Perf at 1140' with (4) 1/2" JH 90° phase. Establish circulation. Set cement retainer at 1079', test tubing 3000#. Pump 350 sacks Class "C" with .5% Halad 9. Circulate cement and close surface valve to squeeze. Cap cement retainer with 35' of cement. Spot 50' surface plug. Install dry hole marker. Clean and clear location.

24 HOUR NOTIFICATION IS REQUIRED

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jamal A. Lawrence TITLE Area Engineer DATE 1-27-83

ORIGINAL SIGNED BY EDDIE SEAY

APPROVED BY _____ TITLE _____ DATE JAN 31 1983CONDITION OF APPROVAL IF ANY
OIL & GAS INSPECTOR

RECEIVED

JAN 28 1983

C.C.D.
HOBBS OFFICE