

INSTRUCTIONS

This form is to be filled with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filled in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

Rustler 1,048							
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"				
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"				
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"				
T. Yates 2,511	T. Miss	T. Cliff House	T. Leadville				
T. 7 Rivers 2,765	T. Devonian	T. Menefee	T. Madison				
T. Queen 3,192	T. Silurian	T. Point Lookout	T. Elbert				
T. Grayburg 3,478	T. Montoya	T. Mancos	T. McCracken				
T. San Andres 3,808	T. Simpson	T. Gallup	T. Ignacio Qtzte				
T. Glorieta 4,893	T. McKee	Base Greenhorn	T. Granite				
T. U Paddock 5,060	T. Ellenburger	T. Dakota	T.				
T. L Paddock 5,174	T. Gr. Wash	T. Morrison	T.				
T. Blinbry 5,412	T. Granite	T. Todilto	T.				
T. Tubb	T. Delaware Sand	T. Entrada	T.				
T. Drinkard	T. Bone Springs	T. Wingate	T.				
T. Abo	T.	T. Chinle	T.				
T. Wolfcamp	T.	T. Permian	T.				
T. Penn.	T.	T. Penn. "A"	T.				
T. Cisco (Bough C)	T.						

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	713	713	Red Bed				
713	1,070	357	Red Bed & Anhy				
1,070	1,178	108	Anhy				
1,178	2,583	1,405	Salt & Anhy				
2,583	3,818	1,235	Anhy				
3,818	4,264	446	Anhy & Lime				
4,264	4,390	126	Lime				
4,390	4,628	238	Anhy & Lime				
4,628	4,855	227	Lime				
4,855	4,974	119	Lime & Sand				
4,974	5,202	228	Lime				
5,202	5,800	598	Lime & Shale				
	5,800		TD				