

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPI
(Other instructions
verse side)TE*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NE-0241

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cities Service Federal

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Jalmat11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**Sec. 35, T24S, R36E**

12. COUNTY OR PARISH

Lee

13. STATE

NM1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

HMA Production Company

3. ADDRESS OF OPERATOR

c/o Oil Reports & Gas Services, Inc., Box 763, Hobbs, NM 882404. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface**990' FSL & 330' FSL of Sec. 35**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3252.3 OR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded with rat hole machine 11/19/75. Drilled 32' of 16" hole & ran 30' of 12 3/4" 42# conductor pipe. Cemented around outside of pipe with 1 yard (approx 25 sacks) cement.

Rigged up rotary rig & spudded rotary hole 11/21/75. Cemented 8 5/8" 28# casing at 868 with 400 sacks class "C" cement, 2% calcium chloride & 1/4# floccle per sack. Plug down 7:45 AM 11/22/75. Circulated out approximately 100 sacks. WOC 12 hours, tested casing with 800# for 30 minutes, test O.K.

Cemented 5 1/2" 17# casing at 3269 with 150 sacks Halliburton lite with 8# salt & 1/4# floccle per sack & 250 sacks Class "C", 8# salt per sack 0.5% CFR-2. Plug down 11:00 AM 12/1/75. Top cement by temperature survey 1500". WOC 72 hours, tested casing with 1500# for 30 minutes, test O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

12/8/75

(This space for Federal or State office use)


APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.