Submit 3 Copies to Appropriate District Office

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

District Office OIL CONSERVATION DIVISION DISTRICT I WELL API NO. P.O. Box 1980, Hobbs NM 88240 P.O. Box 2088 30-025-25236 Santa Fe, New Mexico 87504-2088 **DISTRICT II** 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 STATE [FEE X DISTRICT III 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) WOOLWORTH, C. D. 1. Type of Well: GAS WELL WELL [OTHER SWD 8. Well No. 2. Name of Operator 019 Phillips Petroleum Company 9. Pool name or Wildcat 3. Address of Operator 4001 Penbrook Street, Odessa, TX 79762 JALMAT-YATES-7R 4. Well Location NORTH 2310 WEST 1650 Feet From The Line Feet From The Line and Unit Letter LEA 36-E **NMPM** County Township Range 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3328' RKB Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: **NOTICE OF INTENTION TO:** X ALTERING CASING PLUG AND ABANDON REMEDIAL WORK PERFORM REMEDIAL WORK COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CHANGE PLANS TEMPORARILY ABANDON CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** OTHER: . OTHER: _ 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. THIS IS A RULE 118 WELL. MIRU SIERRA WELL SERVICE, OBTAIN PUMP IN RATE ON 2-7/8" TBG INTO PERFS 3230'-3270'. ALL CEMENT PLUGS ARE CLASS "C" MIXED AT 14.8 PPG SQZ PLUG NO. 1, 75 SXS, 3200'-3270', SHUT-IN OVERNIGHT, COVERS SEVEN RIVERS. CHECK FOR PRESSURE, COOH W/PKR & TBG, GIH W & TAG TOC, CIRC 5-1/2" CSG W 9.5 PPG MUD-LADEN FLUID. SPOT PLUG NO. 2, 60 SXS, 3200'-2720', COVERS YATES & TANSILL. 6. FREEPOINT & PULL 5-1/2" CSG, NEED TO PULL 1400'. 7. SPOT PLUG NO. 3, 75 SXS, 1450'-1283', WOC & TAG, COVERS SALT TOP & 8-5/8" SHOE. 8. SPOT PLUG NO. 4, 35 SXS, 300'-3'. 10. CUT OFF CSG, INSTALL MONUMENT MARKER, PERFORM RECLAMATION WORK. I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE Senior Regulation Analyst DATE 04/19/96 SIGNATURE TELEPHONE NO. (915) 368-1488 TYPE OR PRINT NAME ATTY (This space for State Use) ORIUMAL SIGNADAY LEGRA SEXTON APR 2.3 1996 DISTRICT FEDERATOROM TITLE APPROVED BY

×

K.OYETT

24