

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42 R1424.  
LEASE DESIGNATION AND SERIAL NO.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT..." for such proposals.)

RECEIVED

LC 032450 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

South Mattix Unit

8. FARM OR LEASE NAME

South Mattix Unit

9. WELL NO.

27

10. FIELD AND POOL, OR WILDCAT

Fowler Upper Yeso

11. SEC., T., R., M., OR BLE. AND  
SURVEY OR AREA

15-24-37 NMPM

12. COUNTY OR PARISH

Lea

13. STATE

NM

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Drawer A, Levelland, TX 79336 U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

2030' FNL X 1880' FWL Sec. 15 (Unit F, SE/4 NW/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3250.4 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spud ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☒(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

On 9/28/77 Hillin Drilling Co. (Rig #3) spudded a 12 1/4" hole at 7:30 P.M. Drilled to TD of 1026' and set 9 5/8" casing at 1026'. Cement with 375 SX Econdite and 100 SX Class "C" cement with 2% salt. Plugged down at 1:45 A.M. 9/30/77. Circulated 50 SX. WOC 18 Hrs. Test casing with 1000# for 30 minutes. Test ok.

Reduced hole to 8 3/4" and resumed drilling.

RECEIVED

OCT 11 1977

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Randy AtkinsTITLE Staff Assistant (SG)DATE 10-5-77

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

ACCEPTED FOR RECORD

OCT 12 1977

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side