

1 cc  
NMOCD

COPY TO O.G.S.

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other P X A

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
P. O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL X 2310' FEL, Sec. 26  
AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4)  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
LC-032451 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Myers B

9. WELL NO.  
3

10. FIELD OR WILDCAT NAME  
Jalmat Yates

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
26-24-36

12. COUNTY OR PARISH  
Lea

13. STATE  
NM

14. API NO.  
3330.6 RDB

15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO:      SUBSEQUENT REPORT OF

TEST WATER SHUT-OFF      

FRACTURE TREAT      

SHOOT OR ACIDIZE      

REPAIR WELL      

PULL OR ALTER CASING      

MULTIPLE COMPLETE      

CHANGE ZONES      

ABANDON\*      

(other)      

RECEIVED

JUN 17 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)  
U.S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in service unit 5-1-81. Ran cast iron bridge plug and set at 2800'. Displaced hole with 10 lb. brine gel. Spotted 12 sacks cement plug. Raised tubing to 2000'. Tag plug at 2710'. Raise tubing to 1370' and spotted 25 sacks cement plug. Raised tubing to 96' and spotted 12 sacks cement plug. Circulated 3 sacks. Installed P X A marker.

0+4-USGS, H      1-Hou      1-Susp      1-GPM      1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct  
SIGNED Greg Mitchell TITLE Admin. Analyst DATE 6-15-81

APPROVED (This space for Federal or State office use)  
(Orig. Sgd.) PETER W. CHESTER TITLE \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED BY \_\_\_\_\_ CONDITIONS OF APPROVAL, IF ANY:  
NOV 5 1981  
FOR JAMES A. GILLHAM DISTRICT SUPERVISOR \*See Instructions on Reverse Side

RECEIVED  
NOV 8 1982  
S.C.D.  
HOBBES OFFICE