

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐ **APR 7 1981**
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
P. O. Box 68 Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL & 2310' FEL, Sec. 26
AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4)
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input checked="" type="checkbox"/>		<input type="checkbox"/>
(other)			

5. LEASE
LC-032451-b
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Myers B
9. WELL NO.
3
10. FIELD OR WILDCAT NAME
Jalmat Yates
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
26-24-36
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3330.6 RDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon well per the following:

Set a cast iron bridge plug at 2800' and cap with 58' (6 SX) Class C cement.
Set a 240' (25 SX) Class C cement plug from 1130'-1370'.
Set a 96' (10 SX) Class C cement surface plug and erect a P X A marker.

0+4- USGS, H 1-Hou 1-Susp 1-GLF 1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Gerald L. Foster TITLE Admin. Analyst DATE 3-27-81

APPROVED BY PETER W. CHESTER (Orig. Sgd.) TITLE _____ DATE _____
(This space for Federal or State office use)

CONDITIONS OF APPROVAL, IF ANY:

APR 9 1981

JAMES A. GILLHAM
DISTRICT SUPERVISOR
See Instructions on Reverse Side

OIL CONSERVATION DIV.

APR 14 '81

RECEIVED