

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & 2310' FEL, (Unit B NW/4
AT TOP PROD. INTERVAL: NE/4, Sec 26)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other)

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☒
☐

5. LEASE

LC-032451-b

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Myers B

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Jalmat Yates

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

26-24-36

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
333Q6 RDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Abandoned Seven Rivers Zone by setting Cast Iron Bridge Plug at 3150' with 35' cement. Perforated Yates Gas Zone 2890'-94', 2897'-2906', 2912'-16', 2932'-60', 2984'-94', 3009'-11', 3015'-19', 3034'-38', 3044'-46', 3050'-52', 3055'-57', with 2 DP JSF. Ran tubing to base of perfs at 3075' and spotted 100 gallons 15% MCA acid. Raised tubing to 2890'. Acidized and fraced in 3 stages with 3200 gallons 15% MCF acid with CO₂ and 30,000 gallons of Gel and 61500# 20/40 sand and 48000# sand and 3000# rock salt. Currently evaluating additional completion.

RECEIVED

AUG 29 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO
Set @ _____ Ft.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray Cox

TITLE Admin. Supervisor

DATE 8-27-79

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

0+4 USGS -H, 1-Div, 1-Susp, 1-BD

