Form 9-331 Dec. 1973

e de la composição de l

Form Approved.

UNITED STATES	Budget Bureau No. 42-R1424
DEPARTMENT OF THE INTERIOR	5. LEASE
GEOLOGICAL SURVEY	NM-7488 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
decedione solve!	- N. INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
	- B. FARM OR LEASE NAME
1. oil gas well other	Myers B Federal RA/A 9. WELL NO.
2. NAME OF OPERATOR	28
Amoco Production Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Langlie Mattix Queen
P. O. Box 68, Hobbs, NM 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 330' FSL x 420' FWL, Sec. 9	9-24-37
AT SURFACE: (Unit M. SW/4 SW/4)	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	LeaNM
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF -	1 12/17/1
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	o 1080
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL SHOULD OR ALTER CASING	(NOTE PRINTEY esults of multiple completion or zone GICAL COMPER ON Form 9-330.) NEW MEXICOSE ON FORM 9-330.)
PULL OR ALTER CASING	(NOTE PRIME results of multiple completion or zone GICAL Charge on Form 9–330.) NEW MEXICONE
CHANGE ZONES U. S. GEOGR	NEW MICH
HEADON.	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	trootionally drillad with authorities to the
Moved in service unit 2-1-80. Ran a retrieval Perforated 2776'-94', 2800'-14', 2820'-30', 2936'-42' with 2 JSPF. Ran tubing, packer, a Tailpipe at 2760'. Acidized with 7750 gal 183% KCL water. Currently shut-in evaluating of	2840'-52', 2855'-60', 2890'-2902', and tailpipe. Packer set at 2580' 5% LSTNE acid. Flushed with 18 bb
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED BOULD TITLE ASSIST Admin.	Ann. 0.05.00
	Ana date 2-25-80
(This space for feet at) ff	FOR*RECORN
APPROVED BY	DATE
1 ++R 2	8 1980 -
0+4 USGS-H, 1-Hou, 1-Susp, 1-BD U. S. GEOLOGI	ICAL CURRENT
HOBBS, NET	W MEYICO
*See Instructions on Reverse S	ide MENICO