and the second second

A. Sofia

-

Form	Approved.	
Rudge	et Rureau No	42-R142

Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-7488
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir, Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	Myers B Federal 9. WELL NO.
2. NAME OF OPERATOR	28
Amoco Production Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P. O. Box 68, Hobbs, NM 88240	Langlie Mattix Queen 11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) 330' FSL & 420' FWL, Sec. 9 AT SURFACE: (Upit M SW// SW//)	9-24-37
AT SURFACE: (Unit M, SW/4 SW/4) AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE NM
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3267 1 GR
REQUEST FOR APPROVAL TO:  TEST WATER SHUT-OFF  TEST WATER SHUT-OFF  TEST WATER SHUT-OFF	3 - B
FRACTURE TREAT	A0711
REPAIR WELL	1919 CAL NSTERMED of multiple completion or zone WEXICO ange on Form 9–330.)
PULL OR ALTER CASING   MULTIPLE COMPLETE  GEOLOGI	CA!(NSTIRNE) or results of multiple completion or zone W MEXICO ange on Form 9–330.)
MULTIPLE COMPLETE U. S. GLOS, NE HOBBS, NE	. A4
ABANDON*	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertiner. On 10-11-79 Cactus Drilling Co. (Rig #63) spun Drilled to a TD of 1102' and ran 9-5/8" casin 400 sx Class C cement with additives and 100 CACL. Plug down 7:15 P.M. 10-13-79. Circulatesing with 750# for 30 min. Test OK. Reduce	lirectionally drilled, give subsurface locations and it to this work.)*  ud a 12-1/4" hole 12:00 noon.  ng set at 1102'. Cement with  sx Class C cement with 2%  ated 15sxWOC 18 hrs. Test
resumed drilling.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED BOU DOWN TITLE ASSIST. Admin	RECORD 10-18-79
(This space for the State off	ice use)
APPROVED BY	2 191 SURVEY
See Instructions on Reverse S	

\*See Instructions on Reverse Side