

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒
well well other

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1980' FEL & 660' FSL, Sec. 9

AT SURFACE: (Unit 0, SW/4 SE/4)

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐RECEIVED
OCT 22 1979U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE

NM-7488

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Myers B Federal

9. WELL NO.

29

10. FIELD OR WILDCAT NAME

Langlie Mattix Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

9-24-37

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3271.3 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 9-29-79 Cactus Drilling Co. (Rig #63) spudded a 12-1/4" hole at 11:00 P.M. Drilled to a TD of 1108' and ran 9-5/8" casing set at 1108'. Cemented with 400 sx Class C cement with additives and 100 sx Class C cement with 2% CACL. Plugged down at 3:15 P.M. 10-1-79. Circulated 37sx. WOC 18 hrs. Tested casing with 750# for 30 min. Test OK. Reduced hole to 8-3/4" and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Bob Davis

TITLE

ASSISTANT

DATE

10-18-79

(This space for Federal or State use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

0+4 USGS-H, 1-Hou, 1-Susp, 1-BD

ACCEPTED FOR RECORD
OCT 22 1979
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO