COPY TO O. C. C. **, ----**

< ÷ :

19. 19. seg⁴⁴, 19. 19. seg⁴⁴, 19. seg

Sec.

en en de la composition de la compositi

Definer?

BALENDARD COMPANY

Dec. 1973	Form Approved. Budget Bureau No. 42–R142
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	+6-032181-b NMD. 321613
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	South Mattix Unit Fed.
reservoir, Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil ☆ gas □ other	South Mattix Unit Fed.
2. NAME OF OPERATOR	9. WELL NO. 38
Amoco Production Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	<u>Fowler</u> Drinkard
P. O. Box 68, Hobbs, NM 88240	11. SEC., T., R., M., OR BLK. AND SURVEY O
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) 750' FNL x 750' FEL, Sec. 15	15-24-37
AT SURFACE: (Unit A NE/A NE/A)	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Lea NM
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WE
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3246.3 GL
TEST WATER SHUT OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
PULL OR ALTER CASING	NOTE: Report results of multiple completion or zor
	Grange on Form 9-330.)
	1080
(other) U. S. GEOLOGIC	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	MEXICO
including estimated date of starting any proposed work. If well is di	all pertinent details, and give pertinent dates rectionally drilled, give subsurface locations and
including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinent	t to this work.)*
in 1-29-60 verna Drilling Company (Rig #12) si	pudded a 12-1/4" hole at 6:00 P
Drilled to a TD of 845' with a deviation of 7	°. Propose to skid rig 50' ea
and spud well #384. All plans will remain the	e same as South Mattin Unit #20
Propose to P x A well #38 by spotting a 125 st across top of Anhydrite and a 20 cy Class H	x Class H cement plug 750'-650'
across top of Anhydrite and a 20 sx Class H co	ement surface plug.
Subsurface Safety Valve: Manu. and Type	Set @ F
18. I hereby certify that the foregoing is true and correct	
SIGNED BOU Davis TITLE Assist. Admin.	Ann
(This space for Federal or State offic	
CONDITIONS OF APPROVAL, IF ANY:	DATE
EB 7 1980 T	
0+4 USGS-H, 1-Hou, 1-Susp, 1-BD, 1-ARCO	

*See Instructions on Reverse Side

- +



an 1, arata1 - 1