30-025-26730

	COPY TO O. C. C.	
	Form 9-331 Dec. 1973 UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	30-02 ³⁷ 3673 Form Approved. Budget Bureau No. 42-R1420 5. LEASE <u>+C~032181-b</u> NM0.321613 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a difference of the form 9-331-C for such proposals.)	S 7. UNIT AGREEMENT NAME erent South Mattix Unit Fed.
	1. oil gas well ⊠ well □ other	8. FARM OR LEASE NAME South Mattix Unit Fed, 9. WELL NO.
	 NAME OF OPERATOR Amoco Production Company ADDRESS OF OPERATOR 	10. ELE DOR WILDCAT NAME Fowler Drinkard
	 P. O. Box 68, Hobbs, NM 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space below.) 750' FNL x 700' FEL, Sec. 15 AT SURFACE: (Unit of NE (A)) 	11. SEC., T., R., M., OR BLK. AND SURVEY O AREA 15-24-37
	AT TOP PROD. INTERVAL: (Unit A NE/4 NE/4) AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE
	16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTI REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WC
	REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF I FRACTURE TREAT I	<u> </u>
	SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
	and spud well #38Y All plans will newsin	is directionally drilled, give subsurface locations and inent to this work.)*) - spudded a 12 1/4" hole at 6:00 P: f 7°. Propose to skid rig 50' eas
	teron ton of Ashuduite and a 20 au Cl	the same as South Mattix Unit #38. 5 sx=Glass H cement plug 750'=650' H-cement surface plug.
	No new surface disturbance	
	Subsurface Safety Valve: Manu. and Type	Set @ F'
	18. Thereby certify that the foregoing is true and correct SIGNED	lin. Aname 2-4-80
APPRO	(This space for Federal or State CONDITIONS OF APPROVAL. IF ANY:	office use)
FEB 2	1980 : 1980 : 19	
GUTTYG DISTRI	ICT ENGINEER	