NTA FE . MEXICO OIL CONSERVATION COMMISSI	Supersedes Old C-102 and C-103
	Effective 1-1-65
LE s.g.s.	Sa. Indicate Type of Lease
AND OFFICE	State Fee X
PERATOR	5, State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	
USC "APPLICATION FOR PERMIT _" (FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Name
OIL X GAS WELL OTHER-	8, Farm or Lease Name
Jame of Operator Lewis B. Burleson, Inc.	Huff
Address of Operator	9. Well No.
Box 2479, Midland, TX 79702	10. Field and Pool, or Wildcat
_ocation of Well G 1650 FEET FROM THE NOTTH LINE AND 1650 FE	Langlie-Mattix
THE <u>east</u> line, section 9 Township 24-S RANGE 37-F	- HMPM: (
15. Elevation (Show whether DF, RT, GR, etc.) 3293.0GR	12. County Lea
Check Appropriate Box To Indicate Nature of Notice, Report NOTICE OF INTENTION TO: SUBSECTION	or Other Data OUENT REPORT OF:
NOTICE OF INTENTION OF	
RFORM REMEDIAL WORK	ALTERING CASING
MPORARILY ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB	T PLUG AND ABANDOHMENT
OTHER	
OTHER	
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, in work) SEE RULE 1 103.	acluding estimated date of starting any proposed
Spudded 9-18-90.	
Set 1047' of 8-5/8", set w/ 350 sx Halliburton Lite, 2% CaCh	, 1/4# flocele, 200 sx
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri Ran 86 joints of 4-1/2", 10.5# casing, set at 3630'. Cemented w/salt, 1/4# flocele. Rig released at 8:00 Pm 9-27-80. Prep to log	300 sx 50/50 poz, 9#
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri	300 sx 50/50 poz, 9#
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri	300 sx 50/50 poz, 9#
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri	300 sx 50/50 poz, 9#
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri	300 sx 50/50 poz, 9#
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri	300 sx 50/50 poz, 9#
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri	300 sx 50/50 poz, 9#
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri	300 sx 50/50 poz, 9#
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri	300 sx 50/50 poz, 9#
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri Ran 86 joints of 4-1/2", 10.5# casing, set at 3630'. Cemented w/salt, 1/4# flocele. Rig released at 8:00 Pm 9-27-80. Prep to lo	300 sx 50/50 poz, 9#
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri	300 sx 50/50 poz, 9# g, perf. & acidize.
Class C, 2% cach, 1/4# flocele. Circulated 12 sx on ground. Dri Ran 86 joints of 4-1/2", 10.5# casing, set at 3630'. Cemented w/salt, 1/4# flocele. Rig released at 8:00 Pm 9-27-80. Prep to log large to the best of my knowledge and belief.	300 sx 50/50 poz, 9# g, perf. & acidize.