

P. O. BOX 1980
HOBBS, NEW MEXICO 88240

0+6-BLM-Roswell, 1-File, 1-Engr RH, 1-Foreman HC, 1-JA, 1-BB, 1-Mr. J.A. - Midland
1-Laura Richardson-Midland

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Injector

2. NAME OF OPERATOR
Getty Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 730, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Unit Ltr. O, 660 FWL & 1980 FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) _____

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐

5. LEASE

NM-7488

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Myers Langlie Mattix Unit

8. FARM OR LEASE NAME

9. WELL NO.

183

10. FIELD OR WILDCAT NAME

Langlie Mattix

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 4, T-24S, R-37E

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3284' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/15/83 Clean out and treat. TD 3750', PBTD 3720'. Rig up. Pull pkr and tbq.
12/16/83 Pull tbq & pkr. Ran 4 3/4" bit tag fill @ 3718', 2' fill clean out to 3720'.
Pull bit ran 5 1/2" arrow @ 3369'.
12/17/83 Set pkr @ 3369'. BJ treated perfs 3460-3694' - 35 holes w/ 5000 gals 73 balls
55 gals checker-sol, max 1560#, min 1500#, A.I.R. 4.2 BPM. ISIP 1140#,
15 min 1040#, swab 1 hour, rec. 36 bbls. Pull pkr.
12/19/83 Ran ADI pkr, 109 jts (3394') 2 3/8" spin coat tbq., displaced w/ treated wtr,
set pkr @ 3401'. Rig down.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Area Superintendent DATE December 21, 1983
Date R. A. [Signature] FOR RECORD

(This space for Federal or State office use)

APPROVED BY [Signature] DATE MAY 8 1984
CONDITIONS OF APPROVAL: MANY

TITLE _____ DATE _____

ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED
MAY 9 1984
O.C.O.
HOBBS OFFICE