GS-Hobbs A. Frnka-Tu	l-B' MLMU ulsa l-J⊔r gr idland l-Filo	COPY TO			•	
Blohm-M Form 9-331 Dec. 1973	9-WIU S			Form Approved. Budget Bureau No. 42–R1424		
	UNITED STATES DEPARTMENT OF THE INTERIOR		5. lease NM 7488			
GEOLOGICAL SURVEY			6. IF INDIAN, A	LLOTTEE OR TRI	BE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different			<b>7. UNIT AGREE</b> Myers Langi	ie Mattix U	nit	
1. Oil			8. FARM OR LE Myers Langl	asename ie Mattix U	nit	
well 2. NAME OF	well other Water Injec		9. WELL NO.	183	6 109 9 18 0 9 18 0 9 18 10	
Getty Oil Company 3. ADDRESS OF OPERATOR P.O. Box 730, Hobbs, NM 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17			10. FIELD OR WI Langlie Mat	tix ,		
			11. sec., t., r., area Sec	4, T-24-S,	R-37-E	
	below.) AT SURFACE: AT TOP PROD. INTERVAL: Defense /980		12. COUNTY OR Lea	PARISH 13. S	TATE NM	
AT TOTAL		NATURE OF NOTICE,	14. API NO.			
	DR OTHER DATA		15. ELEVATION: 3284'		DB, AND WE	
TEST WATER FRACTURE TR SHOOT OR AC REPAIR WELL PULL OR ALT MULTIPLE CO CHANGE ZON ABANDON* (other) COMM	EAT		CIVED 1980 Change of CICAL SURVEY	esults of multiple co on Form 9–330.)	South Start Star Start Start S	
including	E PROPOSED OR COMPLETED OPERATIC estimated date of starting any proposed and true vertical depths for all markers a	work. It well is c	irectionally drilled	tails, and give p , give subsurfac	ertinent date e locations ar	
11/18/80	Hondo spudded 12 낯" hole		-			
11/19/80	Drilled 12¼" hole to 520' Cond. casing and set at 1 Flocele, 2% CaCl, and 175 at 4:45 PM. Circulated 1 for 30 minutes. OK.	blb'. Hall' sxs Class '	"C" cement w	/2% CaCl.	Plug dowr	
Subsurface S	afety Valve: Manu. and Type			Set @		
18. I hereby	certify that the foregoing is true and correc	xt 🛛		11/26/80		
signed Dale	N. CIUCKECC	or Federal or State o		ACCEPTED	FOR RECOR	
APPROVED BY CONDITIONS (	OF APPROVAL, IF ANY:		DATE	DEC	- Lid	
	*See Insi	tructions on Reverse	e Side	U.S. GEOLO ROSWELL,	GICAL SURV	