

5-USGS-Hobbs
 1-W.A. Frnka-Tulsa
 Form 9-331 1-R.W. Blohm-Midland
 Dec. 1973

1-File
 9-WIO's
 1-JDM-Engr.

Form Approved.
 Budget Bureau No. 42-R1424

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☐ well ☐ other Water Injection Well

2. NAME OF OPERATOR

GETTY OIL COMPANY

3. ADDRESS OF OPERATOR

88240
 P.O. BOX 730, Hobbs, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Ltr *D*, 660' FNL & 1980' FWL
 AT TOP PROD. INTERVAL:
 AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Spud and cement

XX

5. LEASE

NM 7488

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Myers Langlie Mattix Unit

8. FARM OR LEASE NAME

Myers Langlie Mattix Unit

9. WELL NO. 204

10. FIELD OR WILDCAT NAME

Langlie Mattix

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 7, T24S, R37E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
 3311' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
 JUN 16 1980
 U.S. GEOLOGICAL SURVEY
 HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/5/80 Hondo spudded 12 1/4" hole at 4:30 P.M.

10/6/80 Drilled 12 1/4" hole to 520'. Ran 11 jts. (495') 8 5/8" 24# K-55 R3 A Cond. Casing and set at 505'. Halliburton cemented w/175 sxs. Lite w/2% CaCl, 1/4# Flocele/sx and 175 sxs. Class "C" cement w/2% CaCl. Total cement 350 sxs. Circulated 84 sxs. cement. Plug down at 5:45 AM WOC.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Dale R. Crockett* TITLE Area Supt.

DATE 10/9/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: