-							
5-	USGS-Hobbs	1-JDM-Engr		·**			
	W.A. Frnka-Tulsa	1-BWI-MIMU					
orm 9-331 l-	R.W. Blohm-Midland	9-WIO's			Approved.		
Dec. 1973	UNITED STATES	F		ා (Budg	et Bureau N	o. 42-R142	24
DEDA			5. LEASE	1911년 - 1911년 1911년 - 1911년 - 1911년 1911년 - 1911년 - 1911년	<u>5</u>		
DEPA	RTMENT OF THE INTERIO	K -	NM 748			333 335	
	GEOLOGICAL SURVEY	1 -	6. IF INDIA	N, ALLOTTEE	OR TRIBE	NAME	
CUNDOV NOT			7 HNUT AC	REEMENT N		<u></u>	·
	FICES AND REPORTS O			Langlie 1		Unit	
eservoir. Use Form 9-331	proposals to drill or to deepen or plug C for such proposals.)	back to a different		R LEASE NAM			·
1. oil gas				Langlie M		Unit	
well XX well	└┘ other		9. WELL N	0.		220	
2. NAME OF OPERA	ATOR		230	2. 문서			
Getty	Oil COmpany		10. FIELD O	R WILDCAT N	AME	366	·
3. ADDRESS OF OP		-		anglie Ma	· · · · · · · · · · · · · · · · ·	्र २ हे	
P.O. B	ox 730, Hobbs, N.M. 88	240	11. SEC., T.	, R., M., OR B	LK. AND S	SURVEY C	DR
E at a state stat	LL (REPORT LOCATION CLEARL		AREA	9, T245-I	275	문 (구분) (같죠.★	
AT SURFACE:	Unit Ltr L, 1980' FSL	& 760'FWL -		OR PARISH			
AT TOP PROD. II			Lea	I UK FAKISH	NM	10 · +	
AT TOTAL DEPTH	l:	[-	14. API NO.	<u>_</u>	 	<u>: ' 신성</u> - 과도과	
	NATE BOX TO INDICATE NATU	RE OF NOTICE,					
REPORT, OR OTH	HER DATA		15. ELEVAT	IONS (SHOW	DF, KDB.	AND W	D)
EQUEST FOR APPRO	OVAL TO: SUBSEQUENT		3265	G.L.		193	-,
EST WATER SHUT-O	_				2 19	1.32	
RACTURE TREAT		RECEI	♥╚!!!!	가 영화 이 이 전 한 이 것 이 전 한 이 것	t j	389	
HOOT OR ACIDIZE			ري – ^ا	가 될 것 같이 같이 가 가 가 가 가 다 다 다 다 다 다 다 다 다 다 다 다 다 다		Teng III	
EPAIR WELL		INUV 12	1980E: Repo	ort results of mu	itiple compl	etion or zo	ne
ULL OR ALTER CAS		-	chan	ge on Form 9-3	330.)		
OF LE COMPLETE							
HANGE ZONES	· H H u	J. S. GEOLOGICA	AL SURVEY				
HANGE ZONES BANDON*		J. S. GEOLOGICA HOBBS, NEW			200 Con	00 900-900 900-900	nerg Fing Cing Final Factor Factor Agent
		J. S. GEOLOGICA HOBBS, NEW			er) badica (autorita)	L, JO UMUN 61 SCORID GN COURD	nang Ang Ding Inna Kasa Nang Nang Nang Nang Nang Nang Nang Nan
BANDON* other)		HOBBS, NEW	MEXICO		an Lagine La Dataon (La	HALL TO UNDER	energy Drag Drag Recons Second Se
BANDON* other) 7. DESCRIBE PROPO		HOBBS, NEW	MEXICO		give pertin	num of the second secon	and Sandara
BANDON* other) 7. DESCRIBE PROPO		HOBBS, NEW	MEXICO		give pertin surface loc	num of the loss of	in Journal and
BANDON* ther) 7. DESCRIBE PROPO including estimate measured and true	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a	HOBBS, NEW DNS (Clearly state work. If well is dire nd zones pertinent	MEXICO all pertinent ectionally dril to this work.)	details, and led, give subs	surface loc	ations an Table Satistications Satis	nđ
ANDON* ther) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a prilled 7 7/8" hole to	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1	MEXICO all pertinent ectionally dril to this work.) L2 jts. (details, and lled, give subs	5/8" 24	ations ar 555 2 3 3 2 4 #∑K−5!	nd 5
BANDON* ther) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set a	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow	MEXICO all pertinent ectionally dril to this work.) L2 jts. (vell ceme	details, and lied, give subs 504') 8 nted w/17	5/8" 24	ations an tions an tions and tions a	nd 5 ₩/2%
BANDON* ther) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80 I	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set a 1/4# Flocele, and 175	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class "	MEXICO all pertinent ectionally dril to this work.) 12 jts. (vell ceme 'C" Cemen	details, and lled, give subs 504') 8 nted w/17 t w/2% Ca	5 sxs.	ations ar 555 2 3 3 2 4 #∑K−5!	nd 5 ₩/2%
BANDON* ther) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80 I	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set a	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class "	MEXICO all pertinent ectionally dril to this work.) 12 jts. (vell ceme 'C" Cemen	details, and lled, give subs 504') 8 nted w/17 t w/2% Ca	5 sxs.	ations an tions an tions and tions a	nd 5 ₩/2%
BANDON* ther) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set 1/4# Flocele, and 175 350 sxs. Plug Down at	HOBBS, NEW DNS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci	MEXICO all pertinent ectionally dril to this work.) L2 jts. (vell ceme 'C" Cemen irculated	details, and lled, give subs 504') 8 nted w/17 t w/2% Ca	5 sxs.	ations an tions an tions and tions a	nd 5 ₩/2%
BANDON* ther) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set 1/4# Flocele, and 175 350 sxs. Plug Down at	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class "	MEXICO all pertinent ectionally dril to this work.) L2 jts. (vell ceme 'C" Cemen irculated	details, and lled, give subs 504') 8 nted w/17 t w/2% Ca	5 sxs.	ations an tions an tions and tions a	nd 5 ₩/2%
BANDON* other) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set 1/4# Flocele, and 175 350 sxs. Plug Down at	HOBBS, NEW DNS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci	MEXICO all pertinent ectionally dril to this work.) L2 jts. (vell ceme 'C" Cemen irculated	details, and lled, give subs 504') 8 nted w/17 t w/2% Ca	5 sxs.	ations an tions an tions and tions a	nd 5 ₩/2%
BANDON* other) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set 1/4# Flocele, and 175 350 sxs. Plug Down at	HOBBS, NEW DNS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci	MEXICO all pertinent ectionally dril to this work.) L2 jts. (vell ceme 'C" Cemen irculated	details, and lled, give subs 504') 8 nted w/17 t w/2% Ca	5 sxs.	ations an tions an tions and tions a	nd 5 ₩/2%
BANDON* other) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set 1/4# Flocele, and 175 350 sxs. Plug Down at	HOBBS, NEW DNS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci	MEXICO all pertinent ectionally dril to this work.) L2 jts. (vell ceme 'C" Cemen irculated	details, and lled, give subs 504') 8 nted w/17 t w/2% Ca	5 sxs.	ations an tions an tions and tions a	nd 5 ₩/2%
BANDON* other) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set 1/4# Flocele, and 175 350 sxs. Plug Down at	HOBBS, NEW DNS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci	MEXICO all pertinent ectionally dril to this work.) L2 jts. (vell ceme 'C" Cemen irculated	details, and lled, give subs 504') 8 nted w/17 t w/2% Ca	5 sxs.	ations an tions an tions and tions a	nd 5 ₩/2%
BANDON* other) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set 1/4# Flocele, and 175 350 sxs. Plug Down at	HOBBS, NEW DNS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci	MEXICO all pertinent ectionally dril to this work.) L2 jts. (vell ceme 'C" Cemen irculated	details, and lled, give subs 504') 8 nted w/17 t w/2% Ca	5 sxs.	ations an tions an tions and tions a	nd 5 ₩/2%
BANDON* ther) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80 I 11/6/80 V	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set a 1/4# Flocele, and 175 350 sxs. Plug Down at WOC 18 hrs. Tested 100	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci 00# for 30 mi	MEXICO all pertinent ectionally dril to this work.) 12 jts. (vell cemen 'C" Cemen irculated ins. OK.	details, and led, give sub 504') 87 nted w/17 t w/2% Ca 150 sxs.	5/8" 24 5 sxs. Cl. Transformed and the system of the syste	ations and the second s	nd 5 w/2% ement
BANDON* other) 7. DESCRIBE PROPC including estimate measured and tru 11/5/80 I 11/6/80 I 11/6/80 I	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set a 1/4# Flocele, and 175 350 sxs. Plug Down at WOC 18 hrs. Tested 100 we: Manu. and Type	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci 00# for 30 mi	MEXICO all pertinent ectionally dril to this work.) 12 jts. (vell cemen 'C" Cemen irculated ins. OK.	details, and lled, give subs 504') 8 nted w/17 t w/2% Ca	5/8" 24 5 sxs. Cl. Transformed and the second states of the second state	ations and the second s	nd 5 ₩/2%
BANDON* other) 7. DESCRIBE PROPC including estimate measured and tru 11/5/80 I 11/6/80 I 11/6/80 I	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set a 1/4# Flocele, and 175 350 sxs. Plug Down at WOC 18 hrs. Tested 100 woc 18 hrs. Tested 100	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci 00# for 30 mi	MEXICO all pertinent ectionally dril to this work.) 12 jts. (vell cemen 'C" Cemen irculated ins. OK.	details, and led, give sub 504') 87 nted w/17 t w/2% Ca 150 sxs.	5/8" 24 5 sxs. Cl. Transformed and the second states of the second state	ations and the second s	nd 5 w/2% ement
BANDON* other) 7. DESCRIBE PROPO including estimate measured and true 11/5/80 11/6/80 Ubsurface Safety Valv 8. I hereby certify that	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set a 1/4# Flocele, and 175 350 sxs. Plug Down at WOC 18 hrs. Tested 100 WOC 18 hrs. Tested 100 at the foregoing is true and correct	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci 00# for 30 mi	MEXICO all pertinent ectionally dril to this work.) 12 jts. (vell cemen 'C" Cemen irculated ins. OK.	details, and led, give sub 504') 87 nted w/17 t w/2% Ca 150 sxs.	5/8" 24 5 sxs. Cl. Tr	ations and the second s	nd 5 w/2% ement
BANDON* other) 7. DESCRIBE PROPO including estimate measured and true 11/5/80 11/5/80 11/6/80 ubsurface Safety Valv 8. I hereby certify that IGNED	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Prilled 7 7/8" hole to ST&C A cond. and set a 1/4# Flocele, and 175 350 sxs. Plug Down at WOC 18 hrs. Tested 100 MOC 18 hrs. Tested 100 where the foregoing is true and correct	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci 00# for 30 mi	MEXICO all pertinent ectionally dril to this work.) 12 jts. (vell cemen 'C" Cemen irculated ins. OK.	details, and led, give subs 504') 87 nted w/17 t w/2% Ca 150 sxs. Set (5/8" 24 5 sxs. Cl. Tr	ations and the second s	nd 5 w/2% ement
BANDON* other) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80 11/6/80 Ubsurface Safety Valv 8. I hereby certify that GNED Dale R.	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Porilled 7 7/8" hole to ST&C A cond. and set a 1/4# Flocele, and 175 350 sxs. Plug Down at NOC 18 hrs. Tested 100 MOC 18 hrs. Tested	HOBBS, NEW ONS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci 00# for 30 mi	MEXICO all pertinent ectionally dril to this work.) 12 jts. (vell cemen 'C" Cemen irculated ins. OK.	details, and led, give subs 504') 87 nted w/17 t w/2% Ca 150 sxs. Set (5/8" 24 5 sxs. Cl. Tr	ations and the second s	nd 5 w/2% ement
BANDON* other) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80 11/6/80 Ubsurface Safety Valv 8. I hereby certify that GNED Dale R.	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Porilled 7 7/8" hole to ST&C A cond. and set a 1/4# Flocele, and 175 350 sxs. Plug Down at NOC 18 hrs. Tested 100 MOC 18 hrs. Tested	HOBBS, NEW DNS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci 00# for 30 mi cea Superinte Federal or State office	MEXICO all pertinent ectionally dril to this work.) 12 jts. (vell cemen 'C" Cemen irculated ins. OK.	details, and led, give subs 504') 8 nted w/17 t w/2% Ca 150 sxs. 150 sxs. Set (11/10/	5/8" 24 5 sxs. Cl. Tr	ations and the second s	nd 5 w/2% ement
BANDON* other) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80 11/6/80 11/6/80 Ubsurface Safety Valv 8. I hereby certify that IGNED	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Drilled 7 7/8" hole to ST&C A cond. and set 1/4# Flocele, and 175 350 sxs. Plug Down at NOC 18 hrs. Tested 100 MOC 18 hrs. Tested 100 MOC 18 hrs. Tested 100 ACC 18 hrs. Tested 100 MOC 18 hrs. Tested 100	HOBBS, NEW DNS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci 00# for 30 mi cea Superinte Federal or State office	MEXICO all pertinent ectionally dril to this work.) L2 jts. (vell ceme 'C" Cemen irculated ins. OK.	details, and led, give subs 504') 8 nted w/17 t w/2% Ca 150 sxs. 150 sxs. Set (11/10/	5/8" 24 5 sxs. Cl. Tr	ations and the second s	nd 5 w/2% ement
BANDON* other) 7. DESCRIBE PROPO including estimate measured and tru 11/5/80 11/6/80 11/6/80 Ubsurface Safety Valv 8. I hereby certify that IGNED	DSED OR COMPLETED OPERATIO ed date of starting any proposed e vertical depths for all markers a Porilled 7 7/8" hole to ST&C A cond. and set a 1/4# Flocele, and 175 350 sxs. Plug Down at NOC 18 hrs. Tested 100 MOC 18 hrs. Tested	HOBBS, NEW DNS (Clearly state work. If well is dire nd zones pertinent 730'. Ran 1 at 516'. Dow sxs. Class " 3:00 P.M. Ci 00# for 30 mi cea Superinte Federal or State office	MEXICO all pertinent ectionally dril to this work.) L2 jts. (vell ceme 'C" Cemen irculated ins. OK.	details, and led, give subs 504') 8 nted w/17 t w/2% Ca 150 sxs. 150 sxs. Set (11/10/	5/8" 24 5 sxs. Cl. Tr	ations and the second s	nd 5 w/2% ement