

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Gulf Oil Corporation 3. Address of Operator P. O. Box 670, Hobbs, NM 88240 4. Location of Well UNIT LETTER <u>M</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>West</u> LINE, SECTION <u>10</u> TOWNSHIP <u>24S</u> RANGE <u>37E</u> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3264' GL	7. Unit Agreement Name 8. Farm or Lease Name S. J. Carr 9. Well No. 10 10. Field and Pool, or Wildcat Fowler Devonian 12. County Lea
--	--

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Sharp spudded 12½" hole at 8 A.M., 10-4-80. TD at 1 P.M., 10-5-80. RU & ran 25 joints 8-5/8" 24# K-55 ST&C (1010') set at 1027'. Cement with 350 sacks "C" w/6% gel & 250 sacks "C" with 2% CaCl₂. Plug down 9:30 P.M., 10-5-80. WOC 18 hrs. Circulate cement. Test casing 1500# 30 min, ok. Drill plug, float & cement. Start drilling formation 7-7/8" hole at 5 P.M., 10-6-80.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. L. Vaughn TITLE Area Drilling Supt. DATE 10-16-80

APPROVED BY Harry Sexton DATE OCT 17 1980

CONDITIONS OF APPROVAL, IF ANY: