

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-75

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER-

Name of Operator  
Amoco Production Company

Address of Operator  
P. O. Box 68, Hobbs, NM 88240

Location of Well  
UNIT LETTER C 660 FEET FROM THE North LINE AND 1830 FEET FROM  
THE West LINE, SECTION 12 TOWNSHIP 21-S RANGE 36-E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name  
McQuatters

9. Well No.  
6

10. Field and Pool, or Wildcat  
Hardy Drinkard

15. Elevation (Show whether DF, RT, CR, etc.)  
3514.7 GL

12. County  
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☒  
OTHER ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐  
OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to change casing program per the following:

HOLE SIZE	CASING SIZE	WEIGHT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17-1/2"	13-3/8"	48#	1300'	Circulate	Surf.
12-1/4"	* 9-5/8"	36#	5100'	Tie back to 13-3/8"	Surf.
8-3/4"	7"	20, 23, 26#	4800'-6900'	Circ. at 4800'	BTM 9-5/8"

\* 9-5/8" intermediate will be run only if lost circulation occurs above top of Glorieta Gas Zone. If no lost circulation is encountered above top of Glorieta, will reduce hole size to 8-3/4" and run 7" casing from surface to TD. Cement will tie back to 13-3/8" casing.

0+4-NMOCD, H 1-Hou 1-Susp 1-W. Stafford, Hou 1-LBG

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Benton Green TITLE Assist. Admin. Analyst DATE 4-6-81

Original Signed by Jerry Sexton DATE 4-6-81  
APPROVED BY Dick J. Supry TITLE  DATE   
CONDITIONS OF APPROVAL, IF ANY: