

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

4-NMOCD-Hobbs  
1-BWI-Foreman  
1-JDM-Engr.  
1-File

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Water injection		7. Unit Agreement Name
2. Name of Operator		Myers Langlie Mattix Unit
3. Address of Operator		8. Farm or Lease Name
P.O. Box 730, Hobbs, NM 88240		Myers Langlie Mattix Unit
4. Location of Well		9. Well No.
UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM		185
THE West LINE, SECTION 3 TOWNSHIP 24S RANGE 37E NMPM.		10. Field and Pool, or Wildcat
		Langlie Mattix
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3255.9 GL		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/21/81 Drilled 7 7/8" hole to TD 3705'. Ran 91 jts. (3689') 5 1/2" OD K-55 14# casing and set @ 3703'. Howco cemented with 950 sxs. Halliburton Lite with 10% salt, 1/4# Flocele, .5% CaCl2, and 200 sxs. Class "C" cement, 65%/35% Poz mix with 2% gel, 2% CaCl2, and 9# salt. Total cement - 1150 sxs. Circulated 275 sxs. WOC.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dale R. Crockett TITLE Area Superintendent DATE 7/23/81

APPROVED BY [Signature] TITLE  DATE

CONDITIONS OF APPROVAL, IF ANY: