

O+5 - USGS - P.O. Box 1857  
Roswell, NM 88201

1 - Engr. Foreman  
1 - File

1 - WIOs  
1 - Engr. Tech.

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR  
Getty Oil Company

3. ADDRESS OF OPERATOR  
P.O. Box 730 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) Commence Drilling Operations

5. LEASE  
NM-7488

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
Myers Langlie Mattix Unit

8. FARM OR LEASE NAME  
Myers Langlie Mattix Unit

9. WELL NO.  
166

10. FIELD OR WILDCAT NAME  
Langlie Mattix

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 4, T-24S, R-37E

12. COUNTY OR PARISH  
Lea

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3266.8 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/2/81 Rigged up Marc Drilling Company. Spudded 12 1/4" hole at 12:00 noon. Drilled 12 1/4" hole to 505'. Ran 12 jts. (484') 8 5/8" OD 24# K-55 ST&C 8 Rd R2 casing and set at 498'. Halliburton cemented with 175 sxs. Lite, 1/4# Flocele & 2% CaCl & 175 sxs. Class C cement w/2% CaCl. Total cement - 350 sxs. circulated 100 sxs.

9/3/81 WOC 18 hrs. Pressured up to 1200# for 30 minutes OK.

(CORRECTED REPORT)

NOV 13 1981

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dale R. Crockett TITLE Area Superintendent DATE 11/10/81

APPROVED BY  
CONDITIONS

NOV 16 1981  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

TITLE DATE