

N. M. L. CONS. COMMISSION
P. O. BOX 1080
HOBBS, NEW MEXICO 88240

O+6 - USGS - Roswell 11 - WIO's
1 - BWI - MLMU - Jal 1 - File

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well well
2. NAME OF OPERATOR
Getty Oil Company
3. ADDRESS OF OPERATOR
P. O. Box 730, Hobbs, New Mexico 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Ltr. N, 660' FSL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
AUG 26 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE
NM-7488
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Myers Langlie Mattix Unit
8. FARM OR LEASE NAME
Myers Langlie Mattix Unit
9. WELL NO.
182
10. FIELD OR WILDCAT NAME
Langlie Mattix
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 4, T-24S, R-37E
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3266.4 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/19/81 Drilled 7 7/8" hole to 3755'. Ran 93 jts. (3740') 5 1/2" 14# K-55 ST&C R-3 casing and set at 3752'. F.C. at 3710'. Dowell cemented with 950 sxs Lite .6% gel, .5% CaCl, 1/4# Flocele, 18% salt, and tailed in with 200 sxs. class "C" cement with 50-50 Poz Mix, 2% CaCl, 18% salt. Total cement - 1150 sxs. Circulated 150 sxs. WOC.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE

Area Superintendent

DATE

August 24, 1981

ACCEPTED FOR RECORD (This space for Federal or State office use)

ROGER A. CHAPMAN

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

AUG 26 1981

U.S. GEOLOGICAL SURVEY See Instructions on Reverse Side