

6 - USGS - Roswell

11 - WIO's

1 - BWI - Foreman

1 - JDM - Engineer

1 - File

1 - BB

Form 9-331

Dec. 1973

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

N. M. OIL CONS. COMMISSION

P. O. BOX 1787  
HOBBS, NEW MEXICO 88240

Form Approved.

Budget Bureau No. 42-R1424

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 730, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit Ltr. P, 660' FSL &amp; 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) commence drilling operations ☒

SUBSEQUENT REPORT OF:

RECEIVED  
OCT 13 1981

OIL &amp; GAS

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/19/81 - Rigged up Marc Drilling Company. Spudded 12 1/4" hole at 2:30 p.m. Drilled 12 1/4" hole to 505'. Ran 12 jts. 8 5/8" 24# K-55 casing and set at 501'. BJ cemented w/175 sxs Lite, 1/4# Flocele, 2% CaCl and 175 sxs class "C" cement w/2% CaCl. Total cement - 350 sxs. Circulated 150 sxs cement.

9/20/81 - WOC 18 hours. Pressured up to 1200# on casing for 30 minutes. O.K.

9/28/81 - Drilled 7 7/8" hole to 3755'. Ran 93 jts. 5 1/2" OD 14# K55 ST&C and set at 3753'. BJ cemented with 900 sxs. Cement w/18% salt, 2% CaCl, 1/4# Flocele and tailed in w/200 sxs. Class "C" 50-50 Poz Mix, 2% CaCl. Total cement - 1100 sxs. Circulated 300 sxs cement. WOC.

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

ACCEPTED FOR RECORD  
ROGER A. CHAPMAN

TITLE Area Superintendent

DATE October 7, 1981

(This space for Federal or State office use)

APPROVED BY

OCT 16 1981

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side