STATE OF NEW MEXICO

ENERGY.	ANO	MINERALS	DEPA	RIMENT

THE PRINTED OF THE PER	LEAD	11415
wa, or corics accrives		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

CONDITIONS OF APPROVAL, IF ANY

Form	C-1	103	
Revis	ed	19-	1 - 7

wa, or corics accrives	OIL CONSERVA	TION DIVISION	
DISTRIBUTION	7		Form C-103 -
SANTA FE	SANTA FE. NEW	X 2088 / MEXICO 87501 x 1980	Revised 10-1-7
FILE	O+2 - NMOCD-P.O. Box	x 1980 I-Foreman-BWI-	MLMU
U.S.G.S.	Hobbs, NM 882	240 11-WIO's	Su. Indicate Type of Lease
LAND OFFICE	l-EngrJDM	l-File	State Fee X
OPERATOR	l-Engr.Tech-BB		5, State Oil & Gas Lease No.
SUNDR	RY NOTICES AND REPORTS ON	SACK TO A DIFFERENT RESERVOIR.	
OIL GAS	ION FOR PERMIT -" (FORM C-101) FOR SUC		7. Unit Agreement Name
WELL WELL	отная. Water Injection	n Well	Myers Langlie Mattix u
. Name of Operator			8. Farm or Lease Name
Getty Oil Compan	У	•	Myers Langlie Mattix u
Address of Operator			9. Well No.
P.O. Box 730, He	obbs, NM 88240		126
Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER A	660 FEET FROM THE North	LINE AND 660 FEET	Ianglie Mattix
East	. 4 34-6	27.7	
THE LINE, SECTI	on 4 Township 24-5	RANGE 3/-E N	mem. []]]]]]]]]]
	15. Elevation (Show whether	DF, RT, GR, etc.)	12. County
	3273.2	' GL	Lea
16. Chark			
	Appropriate Box To Indicate N NTENTION TO:		
" NOTICE OF IT	TENTION TO:	SUBSEQU	ENT REPORT OF:
FERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	
TEMPORARILY ABANDON	. 200 200 2220000	COMMENCE DRILLING OPHS.	ALTERING CASING
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	PLUG AND ABANDONMENT
roce on acten casing	thanke reals		· F
OTHER '	. 🗂	OTHER	
17. Describe Proposed or Completed Op- work) SEE RULE 1103.	perations (Clearly state all pertinent det	ails, and give pertinent dates, inclu	iding estimated date of starting any proposes
work) see Hote 1103.			•
		•	
10/14/81 - Marc Drill:	ing Co. spudded 12¼" hole	e @ 7:00 p.m. Drilled	12½" hole to 505'
Ran 12 jts.	. (489') of 8 5/8" 24# K-	-55 ST&C R3 casing and	set @ 501'. FC @ 458'.
Western cen	mented with 175 sxs. Lite	w/4# Flocele. 2% CaCl	l, and 175 sxs. Class "C"
cement w/29	& CaCl. Total cement - 3	50 sxs. Circulated 9	0 sxs.
,	•		
			•
			•
	•	•	
	•		
	•		
	•		
-			
			•
18. I hereby certify that the information	above is true and complete to the best of	of my knowledge and belief.	
So I horeby contry that the information		Two Cuneminter death	10 (15 (0)