

(July 1989)
(formerly 9-3310)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTCONTACT RECEIPT
OFFICE FOR NUMBER
OF COPIES REQUIRED
(Other instructions on
reverse side)BLM Roswell District
Modified Form No.
NM060-3160-2

30-025-31711

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK

DRILL ☒DEEPEN ☐PLUG BACK ☐

b. TYPE OF WELL

OIL
WELL ☒GAS
WELL ☐

OTHER

SINGLE
ZONE ☒MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

TEXACO EXPLORATION AND PRODUCTION INC.

3a. AREA CODE & PHONE NO.

(915) 688-4620

3. ADDRESS OF OPERATOR

P. O. Box 3109, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface

1650' FSL & 560' FWL, UNIT LETTER: L

At proposed prod. zone

SAME

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

32.5 MILES WEST OF EUNCE, NEW MEXICO

15. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drg. unit line, if any)

560'

16. NO. OF ACRES IN LEASE

1220.75

17. NO. OF ACRES ASSIGNED
TO THIS WELL

43.56

18. DISTANCE FROM PROPOSED LOCATION*
TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT.

1st WELL

19. PROPOSED DEPTH

8600'

20. ROTARY OR CABLE TOOLS

ROTARY

21. ELEVATIONS (Show Whether DF, RT, GR, ETC.)

GR-3701'

Carlsbad Controlled Water Basin

22. APPROX. DATE WORK WILL START *

JULY 1, 1992

23.

PROPOSED CASING AND CEMENTING PROGRAM Secretary's Potash R-111-P Potash

HOLE SIZE	CASING SIZE	WEIGHT/FOOT	GRADE	THREAD TYPE	SETTING DEPTH	QUANTITY OF CEMENT
20	16	65#	H-40	PE	40'	REDIMIX
14 3/4	11 3/4	42#	H-40	ST&C	900'	700 SACKS CIRCULATE
11	8 5/8	32#	K-55 & S-80	LT&C	4550'	1600 SACKS CIRCULATE
7 7/8	5 1/2	15.5# & 17#	J-55	LT&C	8600'	1775 SACKS - SEE STIPS.

CEMENTING PROGRAM: CONDUCTOR - REDIMIX.

SURFACE CASING - 700 SACKS CLASS C w/ 2% Cacl2 (14.8ppg, 1.32f3/s, 6.3gw/s).

INTERMEDIATE CASING - 1350 SACKS 35/65 POZ CLASS H w/ 6% GEL, 5% SALT & 1/4# FLOCELE (12.8ppg, 1.87f3/s, 9.9gw/s). F/B 250 SACKS CLASS H w/ 1% Cacl2 (15.6ppg, 1.19f3/s, 5.2gw/s).

PRODUCTION CASING - 1st STAGE: 775 SACKS 50/50 POZ CLASS H w/ 2% GEL, 5% SALT & 1/4# FLOCELE (14.

2ppg, 1.28f3/s, 5.75gw/s). DV TOOL @ 6000'. 2nd STAGE: 900 SACKS 35/65 POZ CLASS H w/ 6% GEL, 5%

SALT & 1/4# FLOCELE (12.8ppg, 1.87f3/s, 9.9gw/s). F/B 100 SACKS CLASS H (15.6ppg, 1.18f3/s, 5.2gw/s).

THERE ARE NO OTHER OPERATORS IN THIS QUARTER QUARTER SECTION.

TEXACO REQUESTS A VARIANCE FROM ORDER No. 2 REQUIRING A REMOTE CONTROL UNIT FOR A 3M BOP, WE
REQUEST SUBSTITUTING A ROTATING HEAD FOR THE ANNULAR PREVENTER. WE WILL INSTALL TWO OUTSIDE CHOKE
LINES TO A MUD/GAS SEPARATOR IN LIEU OF RUNNING THE LINES TO A PIT AND THE INSIDE BLEED LINE WILL
TERMINATE AT THE MUD/GAS SEPARATOR IN LIEU OF RUNNING TO THE PIT.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone.
If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program,
if any.

24.

SIGNED C.P. Basham / CWH TITLE DRILLING OPERATIONS MANAGER DATE 04-30-92

(This space for Federal or State office use)

PERMIT NO. _____ APPROVAL DATE _____

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

7. INITIAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS

*See Instructions On Reverse Side

TITLE 18 U.S.C. SECTION 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false,
fictitious or fraudulent statements or representations as to any matter within its jurisdiction.