

Bit Program:	12-1/4" hole to 400' 7-7/8" hole to TD	
BOP Program:	0 - 400' 400' - TD	None 3000# WP pipe and blind rams w/ 3000# WP annular preventer and choke manifold
Mud Program:	0 - 400'	Drill w/ a gel/lime slurry. Use paper to control seepage and for sweeps.
	400' - 3350'	Drill with 10# brine water. Circulate through the reserve pit to control solids. Use paper to control seepage and for sweeps.
	3350' - TD	Raise viscosity to 32-34 secs with salt gel. Reduce waterloss to < 15 cc's. Keep pH < 10.
Coring Program:	None planned	
Logging Program:	GR-DLL-MSFL-caliper GR-CNL-lithodensity	
DST Program:	None planned	
Casing Program:	Surface	0 - 400' 8-5/8" 24# K55 STC
	Production	0 - TD 5-1/2" 15.5# K55 STC (roughcoat 500')
Cement program	Surface	Lead 260 sx Cl C + 2% CaCl <sub>2</sub> + 1/4 pps cellophane flakes
	Production	Lead 660 sx Premium Plus w/15 pps salt + 1/4 pps cellophane flakes
		Tail 150 sx 50/50 Poz/Cl C + 2% gel + 3 pps KCl + .3% Halad- 9
		Calculate annular volume from caliper log and adjust volumes if necessary.
Wellhead	8-5/8" 3000# WP Larken "Unistack" casing head 5-1/2" x 2-7/8" 3000# WP Larken "Unistack" tubing head	
H <sub>2</sub> S safety	While drilling below 3000', protective breathing equipment at 2 sites, wind direction indicator, and automatic H <sub>2</sub> S detection and alarm equipment shall be on location. All contractor and company personnel shall be trained in H <sub>2</sub> S safety in accordance with TRC Rule 36.	

RECEIVED

JUL 23 1994

JOHN HUBBS  
OFFICE