

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION  
P.O. BOX 1980  
HOBBS, NEW MEXICO 88240

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

(Other Instructions on reverse side)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. 8910138170 - NM7488	
2. NAME OF OPERATOR OXY USA INC.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. BOX 50250 MIDLAND, TX 79710		7. UNIT AGREEMENT NAME MYERS LANGLIE MATTIX	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 190 FNL 1460 FEL NWNE		8. FARM OR LEASE NAME	
14. PERMIT NO. 30-025-32591		9. WELL NO. 267	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3317		10. FIELD AND POOL, OR WILDCAT LANGLIE MATTIX 7R Q-G	
		11. SEC. T., R., M., OR BLK AND SURVEY OR AREA SEC 6 T24S R37E	
		12. COUNTY OR PARISH LEA	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notices, Report, or Other Data  
NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF  
FRACTURE TREAT  
SHOOT OR ACIDIZE  
REPAIR WELL  
(Other)

☐  
☐  
☐  
☐  
☐

PULL OR ALTER CASING  
MULTIPLE COMPLETE  
ABANDON\*  
CHANGE PLANS

☐  
☐  
☐  
☐  
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF  
FRACTURE TREATMENT  
SHOOTING OR ACIDIZING  
(Other)

☐  
☐  
☐  
☐

REPAIRING WELL  
ALTERING CASING  
ABANDONMENT\*

☐  
☐  
☐  
☒

SPUD, SET SURE CASING & CEMENT  
(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and five pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU RODRIC #10, SPUDDED 12-1/4" HOLE @ 1630HRS MDT 8/9/94, DRILL TO TD @ 398', CHC. RIH W/ 8-5/8" 24# CASING & SET @ 396'. M&P 260sx CL C W/ 2% CACL2 + 1/4# /sx CELLO-FLAKE, DISPLACE W/ FW, PLUG DOWN @ 2235HRS MDT 8/9/94, CIRC 28sx CMT TO PIT, BLM NOTIFIED DID NOT WITNESS, WOC-8HRS. NU BOP & TEST, DRILL OUT & TEST, DRILL AHEAD.

18. Thereby certify that the foregoing is true and correct

SIGNED



TITLE

REGULATORY ANALYST

DATE

8/17/94

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

1994

1994

RECEIVED

OCT 1994

JOHN HODGE  
HODGE