Submit 3 copies to Appropriate District Office

State of New Mexico Minerals and Natural Resources Department

Form C-103 levised 1-1-89

	K
CONSEDUATION DIVISION	

DISTRICT I OIL CONSERVATION DIVISION WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-025-32855 DISTRICT II Santa Fe, New Mexico 87504-2088 Indicate Type of Lease P.O. Box Drawe, DD, Artesia, NM 88210 STATE | FEE | DISTRICT III 6. State Oil / Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELL (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.) COOPER JAL UNIT 1. Type of Well: \times WELL WELL **OTHER** 2. Name of Operator 8. Well No. **TEXACO EXPLORATION & PRODUCTION INC.** 415 3. Address of Operator 9. Pool Name or Wildcat P.O. Box 46510, Denver Colorado 80201-6510 4. Well Location Feet From The NORTH Line and 330 Feet From The WEST Line Section 25 24-S Township.... __ Range <u>__36-E</u>_ _NMPM LEA_ COUNTY 10. Elevation (Show whether DF, RKB, RT,GR, etc.) 3307 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING CHANGE PLANS TEMPORARILY ABANDON COMMENCE DRILLING OPERATION PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: SPUD, SURF CSG, PROD CSG. OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. NABORS RIG #403 SPUD 11 INCH HOLE @ 3:00 PM 05-31-95. DRILLED TO 420'. TD @ 5:30 PM 05-31-95. 1. RAN 10 JOINTS OF 8.5/8, 24#,CF-50, STC CASING SET @ 420'. RAN 4 CENTRALIZERS. DOWELL CEMENTED WITH 250 SACKS CLASS C W/ 2% CACL2 (14.8 PPG, 1.34 CF/S). PLUG DOWN AT 8:45 PM 05-31-95. CIRCULATED 8 SACKS. NU BOP & TESTED TO 1000#. TESTED CASING TO 1000# FOR 30 MINUTES FROM 7:30 AM TO 8:00 AM 06-01-95. WOC TIME 10-3/4 HOURS FROM 8:45 PM 05-31-95 TO 7:30 AM 06-01-95. REQUIREMENTS OF RULE 107, OPTION 2: 1. VOLUME OF CEMENT SLURRY: LEAD 335 (CU. FT.) 2. APPROX. TEMPERATURE OF SLURRY WHEN MIXED: 50 F. 3. EST. FORMATION TEMPERATURE IN ZONE OF INTEREST: 90 F. 4. EST. CEMENT STRENGTH AT TIME OF CASING TEST: 1227 PSI. 5. ACTUAL TIME CEMENT IN PLACE PRIOR TO TESTING: 10-3/4 HOURS. DRILLING 7 7/8 HOLE. DRILLED 7 7/8 HOLE TO 3825'. TD @ 12:00 AM 06-05-95. HLS RAN DLL-MSFL-SONIC, FROM 3830 TO 2700'. SDL-DSN-CSNG FROM 3830' TO 400'. RAN 90 JOINTS OF 5 1/2, 15.5# CF-50, LTC CASING SET @ 3825'. 9. RAIN 90 JOINTS OF 3 1/2, 13.3# OF 30, ETO CASING SET & 3023.

10. DOWELL CEMENTED WITH 615 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (C) 50/50 POZ CLASS H W/ 2% GEL, 5% SALT, 1/4# FLOCELE (14.2 PPG, 1.35 CF/S). PLUG DOWN @ 8101 M 06-05-95. DID NO CIRCULATE CEMENT. RAN TEMPERATURE SURVEY. FOUND TOC @ 1150'. TAGGED PBTD @ 3784'. 12. ND. RELEASE RIG @ 12:30 AM 06-06-95. IIIN 1 6 1995 13. PREP TO COMPLETE. OIL CON. DIV. DIST. 2 I hereby certify that the information above is true and complete to the best of my knowledge and belief. Drilling Operations Mar. SIGNATURE SPC TITLE DATE 6/12/95 TYPE OR PRINT NAME C. P. Basham Telephone No. (303)621-4851

> TITLE DATE

(This space for State Use)

APPROVED BY

Orig. Signed by

Paul Kautz

Geologist

394 25 1985 194 25 1985

AN 15 4 W.