

OPER. OGRID NO. 217
PROPERTY NO. 20479
UNIT POOL CODE 17647
DEPARTMENT 3/3/97
BUREAU OF 30-025-3386.1

ING
BER
RED
n

BLM Roswell District
Modified Form No.

NM060-3160-2

APPLICATION FOR PERMIT TO []

1a. TYPE OF WORK

DRILL ☒

DEEPEN ☐

PLUG BACK ☐

b. TYPE OF WELL

OIL
WELL ☒

GAS
WELL ☐

OTHER

SINGLE
ZONE ☒

MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

STRATA PRODUCTION COMPANY

3a. Area Code & Phone No.

505-622-1127

3. ADDRESS OF OPERATOR

P. O. Box 1030

Roswell, New Mexico 88202-1030

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

At surface

660' FNL & 1980' FEL

At proposed prod. zone

Unit B

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

45 miles west of Jal, New Mexico

15. DISTANCE FROM PROPOSED *
LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.

(Also to nearest drig. unit line, if any)

660'

16. NO. OF ACRES IN LEASE

480.00

17. NO. OF ACRES ASSIGNED
TO THIS WELL

40.00

18. DISTANCE FROM PROPOSED LOCATION*
TO NEAREST WELL, DRILLING, COMPLETED
OR APPLIED FOR, ON THIS LEASE, FT.

3960'

19. PROPOSED DEPTH

9100'

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3695' GR

22. APPROX. DATE WORK WILL START*

February 26, 1997

23.

PROPOSED CASING AND CEMENTING PROGRAM

HOLE SIZE	CASING SIZE	WEIGHT/FOOT	GRADE	THREAD TYPE	SETTING DEPTH	QUANTITY OF CEMENT
17 1/2"	13 3/8"	48#	H-40	8 RD STC	600'	Circ to Surface
11"	8 5/8"	24# & 32#	J-55/S80	8 RD STC	4950'	Circ to Surface
7 7/8"	5 1/2"	17#	K-55	8 RD LTC	9100'	Tie back to 300'

into 8 5/8" casing

Strata Production Company proposes to drill to a depth sufficient to test the Delaware formation. If productive, 5 1/2" casing will be set. If non-productive, the well will be plugged and abandoned in a manner consistent with Federal Regulations. Specific programs as set out in Onshore Oil and Gas Order #1 are outlined in the following attachments:

NMOCD Form C-102 Well Location and Acreage Dedication Plat
Hole Prognosis

Surface Use and Operating Plan
Exhibit "A" Equipment Description
Exhibit "B" Planned Access Roads
Exhibit "C" One Mile Radius Map
Exhibit "D" Drilling Rig Layout Plan

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS
ATTACHED

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24. SIGNED Carol J. Garcia TITLE Production Records Manager DATE 1/30/97

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

APPROVED BY (ORIG. SGD) TONY L. FERGUSON

TITLE

ADM, MINERALS

DATE

2/26/97

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions On Reverse Side

District I
PO Box 1980, Hobbs, NM 88241-1980

District II

PO Drawer DD, Artesia, NM 88211-0719

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-102

Revised February 10, 1994

Instructions on back

Submit to Appropriate District Office

State Lease - 4 Copies

Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number 3D-025-33861		Pool Code 17647	Pool Name Diamondtail Delaware
Property Code 2D478	Property Name AVION FEDERAL		Well Number 1
OGRID No. 021712	Operator Name STRATA PRODUCTION COMPANY		Elevation 3695.

¹⁰ Surface Location





UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	22	23-S	32-E		660	NORTH	1980	EAST	LEA

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County

¹² Dedicated Acres 42	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--	-------------------------------	----------------------------------	-------------------------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

¹⁶ 	¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.  Signature Carol J. Garcia Printed Name Production Records Manager Title January 28, 1997 Date	
	¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. JANUARY 15, 1997 Date of Survey  Signature and Seal of Professional Surveyor.  Certificate Number NM PEAPS NO. 5412	

HOLE PROGNOSIS
FORM 3160-3 APPLICATION FOR PERMIT TO DRILL
STRATA PRODUCTION COMPANY
AVION FEDERAL #1 WELL
660' FNL & 1980' FEL
SECTION 22-23S-32E
LEA COUNTY, NEW MEXICO

In conjunction with Form 3160-3 Application for Permit to Drill, Strata Production Company submits the following items in accordance with Onshore Oil and Gas Order Numbers 1 and 2, and all other applicable federal and state regulations.

1. Geologic Name of Surface Formation:

Permian

2. Estimated Tops of Geologic Markers:

Rustler	1245'	"K" Sand	8590'
B. Anhydrite	4995'	Bone Spring	8880'
Delaware	5050'	T.D.	9100'
Cherry Canyon	6080'		

3. Estimated Depths of Anticipated Fresh Water, Oil or Gas:

Surface	150'	Fresh Water
Delaware	5050' - 9100'	Oil or Gas

No other formations are expected to produce oil, gas or fresh water in measurable quantities. The surface fresh water sands will be protected by setting 13 3/8" casing at 600' and circulating cement back to surface. Any shallower zones above TD which contain commercial quantities of oil and/or gas will have cement circulated across the zone by inserting a cementing stage tool into the 5 1/2" production casing which will be run at TD.

HOLE PROGNOSIS
AVION FEDERAL #1
PAGE 2

4. Casing Program:

<u>Hole Size</u>	<u>Interval</u>	<u>OD Csg</u>	<u>Weight, Grade, Jt. Cond, Type</u>
17 1/2"	0-600'	13 3/8"	48#, H-40, ST&C, New
11"	0-4950'	8 5/8"	24# & 32#, J-55, S-80, LT&C, New
7 7/8"	0-TD	5 1/2"	17#, K-55, LT&C, New

5. Cementing Program:

Surface Casing: 13 3/8" casing will be set at approximately 600' and cemented with approximately 700 sacks of Premium Plus cement with 2% CaCl and additives. The amount may be adjusted depending upon the fluid caliper results, however, cement in sufficient quantities to circulate will be utilized.

Intermediate Casing: 8 5/8" casing will be set at approximately 4950' and cemented with approximately 1900 sacks of 35/65 Poz "C" with additives, and 200 sacks Class "C" with 2% CaCl. The amount may be adjusted dependent upon fluid caliper results, however, cement in sufficient quantities to circulate will be utilized.

Production Casing: If appropriate, 5 1/2" casing will be set at Total Depth. Strata utilizes cement in sufficient quantities to circulate cement into the 8 5/8" intermediate casing in two (2) stages. The first stage to be cemented with approximately 600 sacks 50/50 Poz "H" with additives. The second stage to be cemented with approximately 200 sacks of 35/65 Poz "C" with additives, and 100 sacks of Class "C" Neat.

6. Minimum Specifications for Pressure Control:

The blowout preventer equipment (BOP) shown in Exhibit "A" will consist of a double ram-type (3000 psi WP) preventer and a bag-type (hydril) preventer (3000 psi WP). Both units will be hydraulically operated and the ram-type preventer will be equipped with blind rams on top and 4 1/2" drill pipe rams on bottom. Both BOP's will be nipped up on the 13 3/8" surface casing and used continuously until TD is reached. All BOP's and accessory equipment will be tested to 1000 psi before drilling out of surface casing. Before drilling out of intermediate casing, the ram-type BOP and accessory equipment will be tested to 3000 psi and the hydril to 70% of rated working pressure (2100 psi).

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A 2" kill line and 3" choke line will be included in the drilling spool located below the ram-type BOP. Other accessories to the BOP equipment will include a kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold with 3000 psi WP rating.

7. Types and Characteristics of the Proposed Mud System:

0' to 600'	Fresh water with lime, gel paper and fiber will be used for drilling purposes. Weight 8.4-8.6, Vis 29-36, Ph >8.
600' to 4700'	Saturated brine water purchased from commercial sources with paper and fiber will be utilized. Weight 8.6-10.5, Vis 32-34, Ph 10.
4700' to 9100'	Brine and fresh water purchased from commercial sources with gel and starch, 3% KCL, 20-50 PPM Nitrates, CL 30-75,000, caustic for control and paper for seepage will be utilized. Weight 8.5-8.9, Vis 29-34, Ph 9-10, WL 20-50.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be available at the wellsite at all times.

8. Auxiliary Well Control and Monitoring Equipment:

- A. A kelly cock will be kept in the drill string at all times.
- B. A full opening drill pipe stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times.

9. Testing, Logging and Coring Program:

A two (2) man Mudlogging unit will be on location from top of Delaware formation to TD. Mudlogging unit will be employed from approximately 5050' (Top of Delaware) to 9100' (Total Depth).

If indicated, DLL-MSFL, CNL-Density, Gamma Ray logs, and Caliper logs will be run at TD. The Gamma Ray Dual Laterolog will be run from TD back to the intermediate casing. The Gamma Ray Compensated Neutron Log will be run from TD back to surface. If indicated, Strata may elect to run rotary sidewall cores from selected intervals from approximately 5050' to 9100' dependent upon logging results.

10. Abnormal Conditions, Pressures, Temperatures and Potential Hazards:


No abnormal pressures or temperatures are anticipated. Anticipated bottomhole pressure is 3600# PSI.

Loss of circulation is possible in the Delaware section of the hole, however, no major loss circulation zones have been reported in offsetting wells.

Strata has drilled and completed six (6) wells in the immediate area. To date, Hydrogen Sulfide has not been encountered. However, if Hydrogen Sulfide is encountered, a Hydrogen Sulfide alarm on the drilling rig would be activated. All personnel have had Hydrogen Sulfide training and appropriate breathing apparatus is located on site. If necessary, the well can be shut in utilizing the blow out preventer and other equipment to prevent the migration of Hydrogen Sulfide to the surface.

11. Anticipated Starting Date and Duration of Operations:

Road and location work will not begin until approval has been received from the BLM. The anticipated spud date is February 26, 1995. Once commenced, the drilling operation will be completed in approximately 20 days. If the well is productive, an additional 15 days will be required for completion and testing before a decision is made to install permanent facilities. In conjunction with Form 3160-3, Application for Permit to Drill, Strata Production Company submits the following items in accordance with Onshore Oil and Gas Order Numbers 1 and 2, and all other applicable federal and state regulations.



hydraulic operating system which is to be a closed system. (2) Accumulators with a precharge of nitrogen of not less than 750 PSI and connected so as to receive the aforementioned fluid charge. With the charging pumps shut down, the pressurized fluid volume stored in the accumulators must be sufficient to close all the pressure-operated devices simultaneously within _____ seconds after closure, the remaining accumulator pressure shall be not less than 1000 PSI with the remaining accumulator fluid volume at least _____ percent of the original. (3) When requested, an additional source of power, remote and equivalent, is to be available to operate the above pumps, or there shall be additional pumps operated by separate power and equal in performance capabilities.

The closing manifold and remote closing manifold shall have a separate control for each pressure-operated device. Controls are to be labeled, with control handles indicating open and closed positions. A pressure-reducer and regulator must be provided for operating the Hydral Preventer. When requested, a second pressure-reducer shall be available to limit operating fluid pressures to non-preventers. Gulf Legion No. 38 hydraulic oil, or equivalent or better, is to be used on the fluid to operate the hydraulic equipment.

The choke manifold, choke flow line, relief line, and choke lines are to be supported by metal stands and adequately anchored. The choke flow line, relief line, and choke lines shall be constructed as straight as possible and without sharp bends. Easy and safe access is to be maintained to the choke manifold. If deemed necessary, walkways and stairways it all be erected in and around the choke manifold. All valves are to be selected for operation in the presence of oil, gas, and drilling fluid. The choke flow line valves and relief line valves connected to the drilling spool and all ram type preventers must be equipped with stem extensions, universal joints if needed, and hand wheels which are to extend beyond the edge of the derrick substructure. All other valves are to be equipped with handles.

*To include derrick floor mounted controls.