

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Con
P 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
PENWELL ENERGY, INC. (BILL PIERCE) 915-683-2534

3. Address and Telephone No.
600 NORTH MARIENFELD SUITE 1100 MIDLAND, TEXAS 79701

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
330' FWL & 990' FSL SEC. 19 T18S-R33E LEA CO. NM

5. Lease Designation and Serial No.

LC-069276

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

WEST CORBIN "19" FEDERAL # 6

9. API Well No.

30-025-34007

10. Field and Pool, or Exploratory Area

WILDCAT - Grayburg

11. County or Parish, State

LEA CO. NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☒ Altering Casing
☒ Other and change depth

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- Penwell Energy Inc. requests the approval to change the depth and casing program on the West Corbin "19" Federal # 6.
- Drill 11" hole to 600'. Run and set 600' of 8 5/8" 24# 8-R J-55 ST&C casing. Cement with 550 Sx. of Class "C" cement + 2% CaCl, circulate cement to surface.
- Drill 7 7/8" hole to 5000'. Run and set 5000' of 4 1/2" J-55 10.5# 8-R ST&C casing. Cement with 500 Sx. Of Class "C" Halco light + additives, tail in with 200 Sx. of Class "C" + 2% CaCl, estimate top of cement 400'. (200' inside 8 5/8" surface casing set at approximately 600')

14. I hereby certify that the foregoing is true and correct

Signed

Title Agent

Date 10/14/97

(This space for Federal or State office use)


Approved by

Title

Date

Conditions of approval, if any:

OCT 16 1997



BUREAU OF LAND MGMT.
ROSWELL OFFICE

1997 OCT 15 A 4: 09

RECEIVED