UN. TED STATES I. O. Cother instruction of the contract of the

FORM APPROVED OMB NO. 1004-0136 Expires February 28, 1995

	DEPARTMEN'				CASES OF	5. LEASE DSIGNATION	AND SERIAL NO	
	BUREAU OF	LAND MANAG	ENEN	<u>T</u>)5B -O(3/58	
	CATION FOR PE	RMIT TO D	OR LL	OR DEEPE	EN	6 IF INDIAN, ALLOTTEE	OR TRIBE NAME	
Ia. TYPE OF WORK DR b. TYPE OF WELL	ILL 🛛	DEEPEN [7 UNIT AGRREEMENT NA	AME	
OIL G	AS OTHER				ONE	8. FARM OR LEASE NAME WEI		
2. NAME OF OPERATOR (Conoco Inc.					Warren Un 9. API WELL NO 30~C	it B-T <u>米 了</u> 0 D25-343	
a. Address and telephone no	D 0: 400E 14: "		506			306		
	Dr. Ste 430E, Midland L (Report location clearly a			State requirements	*1	10. FIELD AND POOL, O		
At surface	L (Report location clearly a	1330' FSL 8			,	Warren Blinebry-Ti	ILK.	
At proposed prod. zor	ne K	1330' FSL &				AND SÚRVEY ÓR AR Sec. 26, T20-S	EA	
14. DISTANCE IN MILES A	AND DIRECTION FROM NEA	EST TOWN OR POS	ST O TCE	•		12 COUNTY OR PARISH	13. STATE	
						Lea	NM	
5. DISTANCE FROM PROPO	OSED*		16 NO	OF ACRES IN LEA		F ACRES ASSIGNED HIS WELL		
LOCATION TO NEARES PROPERTY OR LEASE (Also to nearest dr	LINE, FT. lg. unit line, if Any)					40		
8. DISTANCE FROM PROP	OSED LOCATION* RILLING, COMPLETED,		19 PRC	POSED DEPTH	20. ROTA	RY OR CABLE TOOLS		
OR APPLIED FOR, ON TH				6850'		Rotary	DE HILL OWN DOW	
21. ELEVATIONS (Show Wh	nether DF, RT, GR, etc)	25521 CD				3/31/9		
23		3552' GR		GEN GEN WERE IG DE C	CDAN	3/31/3		
	· · · · · · · · · · · · · · · · · · ·			CEMENTING PRO		OHANTITY OF CEME	.m	
SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FO		SETTING DEPTI	MIN	QUANTITY OF CEMENT 565 sxs, circ.		
<u>12-1/4"</u> 7-7/8"	M-50, 8-5/8" K-55, 5-1/2"	17#		6850'	IAS	TNE 280 sxs, circ.		
	11 33,3 1/2				77	HMcGo		
 Proposed Well Pl Cementing Plan. Surface Use Plan. Trailer Mounted BOP & Choke Ma H2S Drilling Ope Surface owner con This application inch The undersigned according to the property of the plane	Rig Layout Drawing. anifold Specifications. rations Plan.	l pad, electric lir , conditions, stip	ne, acce	ss road and flow	APPROVA GENERA SPECIAL ATTACHI line. s concerning op			
deepen directionally, give per	CRIBE PROPOSED PROGRAtinent data on subsurface location	ns and measured and	true vertic	al depths. Give blowou	ut preventer program	, if any.		
J.	Ann Johnse		Pro	perty Analyst			<u>-98</u>	
	deral or State office use)							
PERMIT NO				APPROVAL DATE				
Application approval does	s not warrant or certify that the ap	plicant holds legal or e	quita pie ti	tle to those righs in the	subject lease which v	vould entitle the applicant to co	nduct operations thereor	
APPROVED BY	e in Landon (1944). All All All All All All All All All Al	の で り でん TITLE	Î c	THE ADM W	INFHAL8	DATE	98	
AFFROVED BT		*See Instr	uct ons	On Reverse Sig	de	,		
THE 40 LLC C Cookie	on 1001, makes it a crim se, fictitious or fraudule	a for any nerso	n know	ingly and willfully	/ to make to an	iv department or agen	cy of the	

mf


District I PO Box 1980, Hobbs, NM 88241-1980 District II PO Drawer DD, Artesia, NM 88211-0719 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV PO Box 2088, Santa Fe, NM 87504-2088 State of New Mexico
Energy, Minerals & latural Resources Department

OIL CONSERVATION DIVISION PO Box 2088 Santa Fe, NM 87504-2088 Form C-102
Revised February 21, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

___ AMENDED REPORT

		WE	CLL LC	CATIO	N AND	AC]	REAGE DEDI	CATION PI	LAT		
'API Number 'Pool Code 'Pool Name											
30-0	25.	34369	629	65			rren Blinebry	-Tubb Oil	& Gas		
*Property		,				-	Name			* W	ell Number
003127		,			WARREI	N U	JNIT B-T				306
'OGRID					•		r Name			1	Elevation
0050	73						O INC.				3552'
				1	°Surfac	e]	Location				
UL or lot no.	Section	Township	Range	Lot Idn	Feet from		North/South line	Feet from the	1	1	County
K	26	20-S	38-E		1330)	SOUTH	1330	WE	ST	LEA
		¹¹ B	ottom	Hole	Location	n If	Different F	rom Surfa	ce		
UL or lot no.	Section	Township	Range	Lot Idn	Feet from	the	North/South line	Feet from the	East/We	st line	County
12 Dedicated Acr	es "Joint	or Infill "Co	nsolidatio	n Code 18	Order No.						
4C		1		<u> </u>							
NO ALLOW	ABLE W	ILL BE AS	SIGNET	TO TH	IIS COMP	ET	ION UNTIL ALL	INTERESTS	HAVE B	EEN CO	NSOLIDATED
		ORAN	ON-STA	ANDARD	UNIT HA	1 6	BEEN APPROVE	D BI IUF I	NOTOTAL		
16								¹⁷ OPI	ERATOR	CERT	IFICATION
								II -	•		contained berein is
								true and oc	emplete to the	pest of my	knowledge and belief.
									_	^	
			-						Gin	KAN	son
								Signature	7 1)	
								JO An	n Johnso	on	
									rty Ana	lyst	
								Title			
								3/11/	98		
								Date			
		12321						18 SUI	RVEYOR	CERT	'IFICATION
								I hereby on	riffy that the s	rell location	shown on this plat
							•	11 -			surveys made by me same is true and
								correct to	best of my beli	lef.	
	7	LAT.=32°	32'25"				1		FEBRUA	RY 5,	1998
			03'07'24"					Date of S		AHLFO	(A)
1330	0,				··········			Signature	and seal of	Philippin	an anirveror:
				· ¬ ·					AFGIS!	0075	Y [\$]
	_	}							对副人	02/8	[\$] [
	, F								一一一	₹	Z [\$]
	•	-							70	FECOURING	LAMI
								Certificate	Number	ANDICO-	CO SORWEYOR CONTRACTOR

VICINITY MAP



	· · · · · · <u></u>	''``	
SURVEY	N.M.P.M		
	LEA		
	1330' FSL & 1330		
			•
OPERATOR	3552' CONOCO INC. RREN UNIT B-T NO. 30		•

WEST TEXAS CONSULTANTS, INC.


ENGINEERS-PLANNERS-SURVEYORS

MIDLAND, TEXAS

915-685-3800



LOCATION VERIFICATION MAP



SCALE: 1" = 2000' WTC 45166

SEC. <u>26</u> TWP. <u>20-S</u> RGE. <u>38-E</u>

SURVEY N.M.P.M

COUNTY LEA STATE NM

DESCRIPTION 1330' FSL & 1330' FWL

DESCRIPTION 1330 FSL & 1330 FWL

ELEVATION 3552'

OPERATOR CONOCO INC.

LEASE WARREN UNIT B-T NO. 306

USGS TOPO MAP HOBBS SW, NEW MEXICO - HOBBS SE TEXAS-NEW MEXICO

CONTOUR INTERVAL ___5'


WEST TEXAS CONSULTANTS, INC.

ENGINEERS-PLANNERS-SURVEYORS

MIDLAND, TEXAS

915-685-3800

SECTION 26, TOWNSHIP 20 SOUTH, RANGE 38 EAST, N.M.P.M. **NEW MEXICO** LEA COUNTY.




CENTERLINE DESCRIPTION OF A PROPOSED ELECTRIC LINE:

BEGINNING at a point in an existing electric line, from which point the southwest corner of Section 26, T-20-S, R-38-E, N.M.P.M., Lea County, New Mexico bears N 89° 58' W, 1480.0 feet and S 00° 01' E, 1879.0 feet;

THENCE S 00° 02' 36" W, with the centerline of proposed electric line, 479.1 feet to a point for the end of this line, from which point an anchor easement bears S 00° 0.2' 36" W, 30.0 feet and the southwest corner of Section 26 bears S 00° 01' E. 1399.9 feet and N 89° 58' W. 1478.5 feet

I hereby certify that this plat was prepared from an actual survey made on the ground and meets or exceeds all requirements for land surveys as specified by the state of



Earl Foote Registered Professional Surveyor New Mexico Certificate No. 8278 PROPOSED ELECTRIC LINE TO SERVE WARREN UNIT B-T WELL No. 306


CONOCO INC.

479.1 feet of proposed electric line in Section 26, T-20-S, R-38-E, N.M.P.M., Lea County, New Mexico

WEST TEXAS CONSULTANTS, INC.

ENGINEERS-PLANNERS	MIDLAND, TEXAS	
Survey Date: 2-5-98	Date: 3-4-98	Scale: 1" = 1000'
WTC No. 45166	Drawn By: R.S.	Sheet 1 of 1

SECTION 26, TOWNSHIP 20 SOUTH, RANGE 38 EAST, N.M.P.M. LEA COUNTY. NEW MEXICO



CENTERLINE DESCRIPTION OF A PROPOSED FLOWLINE:

BEGINNING at Conoco Inc. WARREN I JNIT B-T WELL No. 306, from which point the southwest corner of Section 26, T-20-S, R-38-E, N.M.P.M., Le 3 County, New Mexico bears N 89° 58' W, 1330.0 feet and S 00° 01' E, 1330.0 feet;

THENCE with the centerline of proposed flowline as follows: N 89° 55' 37" E, 140.1 feet; N 00° 01' 03" E, 505.3 feet; S 89° 18' 51" E, 589.6 feet; S 00° 57' 07" W, 995.9 feet; N 88° 05' 19" W, 152.6 feet and S 01° 56' 34" W, 181.2 feet to a point at VUBT EAST SEPARATORS, for the end of this line, from which point the southwest corner of Section 26 bears S 00° 01' E, 665.5 feet and N 89° 58' W, 1882.9 feet.

I hereby certify that this plat was prepared from an actual survey made on the ground and meets or exceeds all requirements for land surveys as specified by the state of New Mexico.

WARREN UNIT B-T WELL No. 306
CONOCO INC.

PROPOSED FLOWLINE TO SERVE

2564.7 feet of proposed flowline in Section 26, T-20-S, R-38-E, N.M.P.M., Lea County, New Mexico


WEST TEXAS CONSULTANTS, INC.

ENGINEERS-PLANNERS	MIDLAND, TEXAS			
Survey Date: 2-5-98	Date: 3-4-98	Scale: 1" = 1000"		
WTC No. 45166	Drawn By: R.S.	Sheet 1 of 1		

Earl Holes Resident R

Earl Foote Registered Professional Surveyor New Mexico Certificate No. 8278

SECTION 26, TOWNSHIP 20 SOUTH, RANGE 38 EAST, N.M.P.M. **NEW MEXICO** LEA COUNTY,



CENTERLINE DESCRIPTION OF A PROPOSED ROAD:

BEGINNING at a point in an existing road, from which point the southwest corner of Section 26, T-20-S, R-38-E, N.M.P.M., Lea County, New Mexico, bears N 89° 58' W, 1458.8 feet and S 00° 01' E, 1849.8 feet; THENCE S 00° 00' 08" W, with the centerline of proposed road, 451.6 feet to a point in the northeast corner of well pad for Conoco Inc. WARREN UNIT B-T WELL No. 306, for the end of this line, from which point the southwest corner of Section 26 bears S 00° 01' E, 1398.2 feet and N 89° 58' W, 1458.8 feet.

I hereby certify that this plat was prepared from an actual survey made on the ground and meets or exceeds all requirements for land surveys as specified by the state of New Mexico.

8278 AROFESSIONAL

Earl Foote Registered Professional Surveyor New Mexico Certificate No. 8278

PROPOSED ROAD TO SERVE WARREN UNIT B-T WELL No. 306

CONOCO INC.

451.6 feet of proposed road in Section 26, T-20-S, R-38-E, N.M.P.M., Lea County, New Mexico

WEST TEXAS CONSULTANTS, INC.

ENGINEERS-PLANNER	MIDLAND, TEXAS		
Survey Date: 2-5-98	Date: 3-4-98	Scale: 1" = 1000'	
WTC No. 45166	Drawn By: R.S.	Sheet 1 of 1	

PROPOSED WELL PLAN OUTLINE

GL = 3552'

4-Mar-98

ALL DEPTHS ARE Warren Unit No. 306 WELL NAME BELOW GROUND LEVEL 1330' FSL & 1330' FWL S26-T20S-R38E LOCATION FORMATION MUD FRAC PRESSURE WEIGHT & HOLE SIZE 12-1/4 CASING PROBLEMS FORMATION PROGRAM GRAD GRADIENT TYPE DAYS FORMATION & COMMENTS **EVALUATION** MD TVD Possible hole englargement and sloughing Less than 8.3 1000 1:)((() 8-5/8", 23#, M-50 ST&C @ 1400' 565 sx. Circulate Cement Fuetter @ 1300' Fop Salt @ 1400' 10 ppg Brine Washouts in Salt Section 2000 2000 ese than 8.4 Base Salt @ 2600* Possible Deviation Yates @ 2822 7-Rivers @ 3090* 3000 H2S Monitor on at 1500' No Mud Log' Queen 🧈 3650' Penrose @ 38001 Grayburg @ 3995' Mud up with Gel-Starch if 4000 4000 necessary to control losses Possible losses and seepage to TD San Andres @ 4270* 5000 5000 Gloriet = @ 5510 Passible differential sticking through Glorieta Top Tail Cement @ 5700 Blinebry @ 5896* 6000 6000 Tubb M+r @ 6448 16 Starch'-alt gel GR-CAL-CNL-FDC- ALL-DLL-PE @ 6850 2800' - TD Drinkard @ 6738' 1280 sx. Circulate Cement TD @ 6850" 7000 7000 8000 6000

1- hetemo	Du mille
nm Tietema, Staff Engineer 4-Mar-98	Joe Miller, Reservoir Engineer
To church	
Tim Schrieder, Production Engineer 4-Mar-98	



Well Name: Warren Unit #306

Location : 1330' FSL & 1330' FWL Sec 26, T-20S, R-38E, Lea County, New Mexico

Casing Program:

 Surface
 8 5/8"
 casing
 in
 12 1/4"
 Hole
 at
 1400
 ft.

 Production
 5 1/2"
 casing
 in
 7 7/8"
 Hole
 at
 6850
 ft.

Cementing Program:

Surface

Lead	365	sacks	Class C		
Additives	35:65:6 (F	oz:Cem:Gel)	+ 2% CACL2		
	+ 0.25 pp	s Cello-Flake			
Mixed at	12.7	ppg	Yield	1.87	_cuft/sk
-					
Tail	200	sacks	Class C		
Additives	2% A-7P				
Mixed at	14.8	ppg	Yield	1.34	cuft/sk

<u>Production</u>

Tail	260	sacks	Class C		
Additives	1.1% FL-62	+ 1% BA	4-5 <mark>8 + 3% Salt</mark>	+ 0.3%	CD-32
	+ 0.26	SMS			
Mixed at	14.8	ppg	Yield	1.37	cuft/sk
Free Water	0	_%	Fluid Loss _	45	cc/30 min.

SURFACE USE PLAN Cor oco Inc.

Warren Unit B-T #306

The following is required information concerning the possible affect which the drilling of this well may have on the environment, existing road sites, and surrounding acreage. A copy will be posted on the derrick floor so all contractors and sub-contractors will be a ware of all items of this plan.

1. Existing Roads

- A. The proposed well site is 1330' FSL & 1330' FWL, Sec. 26, T20S, R38E
- B. Directions to the location are as follows:

South of Hobbs on Hwy. 18 to ½ mile south of Mile Marker #39; turn east and travel ½ mile; turn north ɛ nd travel ½ mile; turn west and travel ¼ mile; then turn north to location.

C. No improvement or maintenance is anticipated for the existing roads.

2. Planned Access Roads

- A. 451.6' of new access road will be required.
- B. Turnouts as required by surface managing agency.
- C. Culverts as required by surface managing agency.
- D. Gates, cattleguards, or fences as required by surface managing agency.

3. Topographic Map and Well Location

A 7.5" quadrangle topo map was filed with the NOS.

4. Additional Rights-of-Way

Electric line, access road and flowline as shown on attached plats.

5. Water Supply

Fresh and brine water will be obtained from Goldstar's Water Station located 1 mile north of Eunice, NM, and will be trucked to location by the same directions for reaching the drilling site.

6. Source of Construction Materials

Construction materials will be obtained from the SE/4 SE/4, Sec. 15, T20S, R38E, Lea County, NM.



7. Methods of Handling Waste Disposal

- A. The drill cuttings, fluids and completion fluids will be placed in the reserve pit. The reserve pit will be fenced on three sides away from the pad during drilling and the fourth side fenced as soon as the rig moves out. The reserve pit will be allowed to dry, and materials remaining in the reserve pit buried. The reserve pit will be backfilled, leveled and contoured so as to prevent any materials being carried into the watershed. Upon completion, the pad will be leveled, contoured, and reseeded with the appropriate seed mixture as specified by the surface managing agency.
- B. All garbage and trash will be hauled away to designated landfill by Conoco.
- C. Chemical toilets will be provided and n aintained during drilling operations.

8. Ancillary Facilities

No ancillary facilities are planned.

9. Wellsite Layout

See attached Wellsite Layout. The V-door faces East. The reserve pit will be lined with plastic and the pad and pits are staked. All unguarded pits containing liquids will be fenced and any unguarded pit containing liquids will be fenced.

10. Plans for Restoration of Surface

Reserve pits will be rehabilitated once dril ing fluids have been allowed to evaporate to the point the pits are dry enough for backfilling and leveling. In the event drilling fluids will not evaporate in a reasonable time period, the fluids will be removed and transported by tank truck to a state approved disposal facility. Backfilling and leveling of the location will be completed within a time period of one year upon cessation of drilling operations.

11. Surface Ownership

The surface ownership is Robert A. McCasland and Dallas M. McCasland.

12. Archeological Clearance

An archeological survey is being conducted and will be provided upon completion.

13. Operator's Representative and Certification

The person who can be contacted concerning compliance of this Surface Use Plan is:

Mike L. Mankin 10 Desta Drive, Suite 430E Midland, Texas 79705 (915) 686-5794



I hereby certify that I, or persons under my direct supervision, have inspected the proposed drilling site; that I am familiar with the conditions which currently exist; that the statements made in this plan, are, to the best of my knowledge, true and correct; and that the work associated with operations proposed herein will be performed by Conoco Inc. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

Mike L. Mankin


Right-of-Way Agent

3-11-98

Thise L. Manken

Date







H2S Safety Contractor

Terrain is flat, and covered with native grasse:

Two of the three WDI (wind direction indicator) locations with be utilize

(Prevailing winds are SW to NE





Choke Manifold


Muster Area No. 2 WDI



Received
Hobbs
OCD


3.00+EZ/

TRAILER - MOUNTED RIG LAYOUT




Received
Received
Hobbs
OCD

BOP SPECIFICATIONS





CHOKE MANIFOLD DIAGRAM



MANIFOLD

☑ Manuel
☐ Hydraulic



H2S DRILLING OPERATIONS PLAN

I. Hydrogen Sulfide Training

All contractors and subcontractors employed by Conoco will receive or have received training from a qualified instructor within the last twelve months in the following areas prior to commencing drilling operations on this well.

- 1. The hazards and characteristics of hydrogen sulfide (H2S)
- 2. Safety precautions
- 3. Operations of safety equipment and life support systems.

In addition, contractor supervisory personnel will be trained or prepared in the following areas:

- 1. The effect of H2S on metal components in the system, especially high tensile strength tubulars are to be used.
- 2. Corrective action and shut-down procedures when drilling or reworking a well, blowout prevention and well control procedures, if the nature of work performed involves these items.
- 3. The contents and requirements of the contingency plan when such plan is required.

All personnel will be required to carry documentation of the above training on their person.

II. H2S EQUIPMENT AND SYSTEMS

1. Safety Equipment

The following safety equipment will be on location:

- A. Wind direction indicators as seen in attached diagram.
- B. Automatic H2S detection alarm equipment (both audio and visual).
- C. Clearly visible warning signs as seen on the attached diagram. Signs will use the words "POISON GAS" and "CAUTION" with a strong color contrast.
- D. Protective breathing equipment will be located in the dog house and at briefing areas as seen in the attached diagram.



2. Well Control Systems

A. Blowout Prevention Equipment

Equipment includes but is not limited to:

- a. pipe rams to accomodate all pipe sizes
- b. blind rams
- c. choke manifold
- d. closing unit
- e. flare line and means of ignition

B. Communication

The rig contractor will be required to have two-way communication capability. Conoco will have either land-line or mobile telephone capabilities.

C. Mud Program

The mud program has been designed to minimize the volume of H2S circulated to surface. Proper mud weight, safe drilling practices, and the use of H2S scavengers when appropriate will minimize hazards when penetrating H2S bearing zones.


D. Drill Stem Tests


There are no drill stem tests proposed for this well.

III. WELL SITE DIAGRAM

A complete well site diagram including the following information is attached:

- 1. Rig orientation
- 2. Terrain
- 3. Briefing areas
- 4. Ingress and egress
- 5. Pits and flare lines
- 6. Caution and danger signs
- 7. Wind indicators and prevailing wind direction





Mike L. Mankin Right of Way Agent Right of Way and Claims Conoco Inc. 10 Desta Drive, Suite 430E Midland, Texas 79705 (915) 686-5794

February 19, 1998

Bureau of Land Management 620 E. Greene Carlsbad, New Mexico 88221

Attn:

Mr. Barry Hunt, Surface Protection Special st

Re:

Settlement for Well Location and Appurtenances

WARREN UNIT B-T, Well # 306

Section 26, T20S, R38E Lea County, New Mexico

Dear Mr. Hunt:

By this letter Conoco Inc. has made settlement, with surface owner, for the construction of the above referenced location and appurtenances.

If you have any questions, please contact me at 9' 5-686-5794.

Sincerely.

Mike L. Mankin