


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

May 29, 1950

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Cities Service Oil Company Hodges "A" Well No. 2 in the _____

Company or Operator Lease
NE SE NE of Sec. 8, T. 24S, R. 37E, N. M. P. M.,
Langlie-Mattix Field, Lea County.

The dates of this work were as follows: May 24, 1950 and May 25, 1950

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on May 23 19 50
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was drilled to a Total Depth of 1842' after having had 8-5/8" casing set at 1180' and cemented with 625 sax. At the depth of 1842' circulation was lost and could not be regained after 3800 sax of cement, & several thousand barrels of water, mud and chemicals had been pumped in hole. A D. C. retainer was run in hole set at 1130' and cemented on top with 25 sax. The 8-5/8" casing was then filled with mud and cemented from 80' to the surface with 25 sax of cement. Location marked and well abandoned.

Witnessed by R. W. Ely Cities Service Oil Company Dist. Supt.
Name Company Title

Subscribed and sworn before me this _____
29 th day of May 19 50
Fred Larson
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name _____
Position District Superintendent
Representing Cities Service Oil Company
Company or Operator

My commission expires February 8, 1954

Address Drawer G., Hobbs, New Mexico

Remarks: APPROVED

MAY 31 1950

Date _____

Name _____
Title _____