

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR  
JOE E. BROWN

3. ADDRESS OF OPERATOR  
P.O. BOX 543, LOVINGTON, NEW MEXICO 88260

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2630' FSL & 2630' FWL OF SEC, 28  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

CHANGE CEMENTING PROGRAM

5. LEASE

NM-0108997-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
FARRELL FEDERAL

9. WELL NO.

22

10. FIELD OR WILDCAT NAME  
CHAVEROO SAN ANDRES

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 28, T. 7 S., R. 33 E.


12. COUNTY OR PARISH  
ROOSEVELT

13. STATE  
NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND LAND)  
4410.8 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

THE APPLICATION FOR PERMIT TO DRILL THE ABOVE DESCRIBED WELL WAS APPROVED  
SUBJECT TO THE STIPULATION THAT THE 4-1/2" CASING BE CEMENTED WITH SUFFICIENT  
CEMENT TO TIE BACK TO THE SURFACE CASING.

IT IS REQUESTED, INASMUCH AS THE SURFACE CASING IS TO BE SET IN THE RUSTLER  
ANHYDRITE WITH CEMENT CIRCULATED, THAT THE ABOVE STIPULATION BE VOIDED AND

THAT APPROVAL BE GIVEN TO CEMENT THE 4-1/2" CASING WITH SUFFICIENT CEMENT TO  
FILL 600 FEET ABOVE THE TOP OF THE PAY ZONE.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Arthur R. Brown*  
APPROVED

Agent

DATE

NOVEMBER 15, 1983

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY

NOV 17 1983